

DRIVER DETAILS

NAME _____
 DATE _____
 EVENT _____
 WEATHER _____
 RESULT _____
 FASTEST LAP TIME _____

NOTES

TOP DECK CONNECTOR YES NO



CHASSIS AND ELECTRICS

CHASSIS Alloy Carbon
 TOP DECK 2.0mm 2.5mm 3.0mm 4.0mm
 BODYSHELL _____
 WING _____
 E.S.C _____
 SERVO _____
 RECEIVER _____
 CELLS _____

MOTOR AND GEARING

MOTOR _____
 ROTOR DIAMETER _____
 TIMING _____
 GEAR PITCH 48DP 64DP
 SPUR SIZE _____
 PINION SIZE _____

TRACK CONDITIONS

GRIP LEVEL High Medium Low
 TYPE Tight Open Mixed
 SURFACE Carpet Tarmac
 CONDITION Smooth Bumpy
 TEMPERATURE _____ °C _____ °F
 VENUE Indoor Outdoor

WHEELS, TYRES AND INSERTS

WHEELS _____
 TYRES _____
 INSERTS _____
 TYRE ADDITIVE _____
 ADDITIVE TIME Front Minutes Rear Minutes
 TYRE WARMERS Yes No Temp °C Time Minutes

FRONT

Spool
 Gear Diff
 Diff Oil cTs

1 Dot - 1.1mm
 2 Dot - 1.2mm
 3 Dot - 1.3mm
 4 Dot - 1.4mm
 5 Dot - 1.5mm

Line In Shimsmm
 Line Out mm

Washersmm

Shimsmm

Droop.....mm
 On 10mm Block
 Ride Heightmm
 Camber.....°
 Toe.....°
 Pivot Block Strap

44.2
 43.5 44.2 46.0

Washersmm
 Washers.....mm

Washersmm

4° R
 4° Yoke
 6° Yoke

SERVO SAVER
 Yes
 No

Washersmm

12mm
 13mm
 14mm

Cap Type Vented Sealed Emulsion
 Oil.....cTs
 Spring.....
 Piston.....
 Drilled Yes No
 Drilled piston Hole Size.....mm
 Shock Length (X).....mm
 Rebound%

Peripheral Damping
 Yes
 No

Alloy Steel Double Joint

Narrow
 Medium (kit)

Washersmm

REAR

Diff Oil cTs

48.1
mm
mm

Medium
 Wide (kit)

Droop.....mm
 On 10mm Block
 Ride Heightmm
 Camber.....°
 Pivot Block Strap

44.2 45.5 46.1

Shims.....mm

Shimsmm

Line In
 Line Out

Washersmm

(2 Pip shown)
 0 Groove
 1 Groove
 2 Groove

Washersmm

Alloy Steel

Washersmm

WheelBase
 Short
 Middle
 Long

Cap Type Vented Sealed Emulsion
 Oil.....cTs
 Spring.....
 Piston.....
 Drilled Yes No
 Drilled piston Hole Size.....mm
 Shock Length (X).....mm
 Rebound%

Peripheral Damping
 Yes
 No