

DRIVER DETAILS

NAME
DATE
EVENT
WEATHER
RESULT
FASTEST LAP TIME

NOTES

TOP DECK CONNECTOR YES NO



CHASSIS AND ELECTRICS

CHASSIS	Alloy <input type="checkbox"/>	Carbon <input type="checkbox"/>		
TOP DECK	2.0mm <input type="checkbox"/>	2.5mm <input type="checkbox"/>	3.0mm <input type="checkbox"/>	4.0mm <input type="checkbox"/>
BODYSHELL				
WING				
E.S.C				
SERVO				
RECEIVER				
CELLS				

MOTOR AND GEARING

MOTOR		
ROTOR DIAMETER		
TIMING		
GEAR PITCH	48DP <input type="checkbox"/>	64DP <input type="checkbox"/>
SPUR SIZE		
PINION SIZE		

TRACK CONDITIONS

GRIP LEVEL	High <input type="checkbox"/>	Medium <input type="checkbox"/>	Low <input type="checkbox"/>
TYPE	Tight <input type="checkbox"/>	Open <input type="checkbox"/>	Mixed <input type="checkbox"/>
SURFACE	Carpet <input type="checkbox"/>	Tarmac <input type="checkbox"/>	
CONDITION	Smooth <input type="checkbox"/>	Bumpy <input type="checkbox"/>	
TEMPERATURE	°C	°F	
VENUE	Indoor <input type="checkbox"/>	Outdoor <input type="checkbox"/>	

WHEELS, TYRES AND INSERTS

WHEELS						
TYRES						
INSERTS						
TYRE ADDITIVE						
ADDITIVE TIME	Front	Minutes	Rear	Minutes		
TYRE WARMERS	Yes <input type="checkbox"/>	No <input type="checkbox"/>	Temp	°C	Time	Minutes

FRONT

Spool
 Gear Diff

Diff Oil cTs

Washersmm

Washers.....mm

4° Yoke
 6° Yoke

Yes
No

SERVO SAVER

Alloy Steel Double Joint

1 Dot - 1.1mm
 2 Dot - 1.2mm
 3 Dot - 1.3mm
 4 Dot - 1.4mm
 5 Dot - 1.5mm

Washersmm

Washersmm

12mm
13mm
14mm

Narrow
 Medium (kit)

Washersmm

Line In
Line Out

Shimsmm

Shims.....mm

Line In
Line Out

Shims.....mm

Cap Type Vented Sealed Emulsion

Oil.....cTs

Spring.....

Piston.....

Drilled Yes No

Drilled piston Hole Size.....mm

Shock Length (X).....mm

Rebound%

Peripheral Damping Yes No

REAR

Diff Oil cTs

48.1

.....mm

.....mm

Washersmm

Washersmm

Alloy Steel

Medium
 Wide (kit)

0 Dot - 1.0mm
 1 Dot - 1.1mm
 2 Dot - 1.2mm
 3 Dot - 1.3mm
 4 Dot - 1.4mm

(2 Pip shown)

0 Groove
 1 Groove
 2 Groove

Washersmm

WheelBase
 Short
 Middle
 Long

Droop.....mm

On 10mm Block

Ride Heightmm

Camber.....°

Pivot Block Strap

Line In
Line Out

44.2 45.5 46.1

Washersmm

Shims.....mm

Shimsmm

Cap Type Vented Sealed Emulsion

Oil.....cTs

Spring.....

Piston.....

Drilled Yes No

Drilled piston Hole Size.....mm

Shock Length (X).....mm

Rebound%

Peripheral Damping Yes No