

DRIVER DETAILS	
NAME	masaki honda
DATE	2011/8/25/26
EVENT	JMRCA Sportsclass
WEATHER	
RESULT	6th
FASTEST LAP TIME	

NOTES	
U4610X2 USE	
U480T USE	



CHASSIS AND ELECTRICS	
CHASSIS	Alloy <input checked="" type="checkbox"/> Carbon <input type="checkbox"/>
TOP DECK	2.0mm <input type="checkbox"/> 2.5mm <input checked="" type="checkbox"/> 3.0mm <input type="checkbox"/> 4.0mm <input type="checkbox"/>
BODYSHELL	ALEX M6 highspeed
WING	PF
E.S.C	HOBBYWING XR-10
SERVO	SANWA P6S-LH
RECEIVER	SANWA RX-482
CELLS	

MOTOR AND GEARING	
MOTOR	R1 WURKS
ROTOR DIAMETER	12.5MM
TIMING	0
GEAR PITCH	48DP <input type="checkbox"/> 64DP <input checked="" type="checkbox"/>
SPUR SIZE	106
PINION SIZE	35

TRACK CONDITIONS	
GRIP LEVEL	High <input checked="" type="checkbox"/> Medium <input type="checkbox"/> Low <input type="checkbox"/>
TYPE	Tight <input checked="" type="checkbox"/> Open <input type="checkbox"/> Mixed <input type="checkbox"/>
SURFACE	Carpet <input type="checkbox"/> Tarmac <input checked="" type="checkbox"/>
CONDITION	Smooth <input checked="" type="checkbox"/> Bumpy <input type="checkbox"/>
TEMPERATURE	°C °F
VENUE	Indoor <input checked="" type="checkbox"/> Outdoor <input type="checkbox"/>

WHEELS, TYRES AND INSERTS	
WHEELS	YOKOMO(control)
TYRES	50REX40(control)
INSERTS	bomber red(control)
TYRE ADDITIVE	mightyp3(control)
ADDITIVE TIME	Front 1 Minutes Rear 1 Minutes
TYRE WARMERS	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Temp 45 °C Time 1 Minutes

FRONT

Diff Oil cTs

Spool Gear Diff

1 Dot - 1.1mm
2 Dot - 1.2mm
3 Dot - 1.3mm
4 Dot - 1.4mm
5 Dot - 1.5mm

Washers 0.5mm

Washers 2mm
Washers 3 mm

4° Yoke 6° Yoke

SERVO SAVER Yes No

Washers 2mm

12mm
13mm
14mm

Alloy Steel Double Joint

Narrow Medium (kit)

Washers 1mm

Line In Shims 0mm
Line Out 0mm

Dropo.....mm
On 10mm Block
Ride Heightmm
Camber.....°
Toe.....° OUT
Pivot Block Strap

44.2 44.2 45.0

Shims 0mm

Cap Type Vented Sealed Emulsion

Oil.....cTs

Spring.....

Piston.....

Drilled Yes No

Drilled piston Hole Size.....mm

Shock Length (X).....mm

Rebound%

Peripheral Damping Yes No

REAR

Diff Oil 7500 cTs

1.2mm 1.2mm

Medium Wide (kit)

0 Groove
1 Groove
2 Groove

Washers 2mm

Washers 1mm

WheelBase Short Middle Long

Alloy Steel

Dropo.....mm
On 10mm Block
Ride Heightmm
Camber.....°
Pivot Block Strap

44.2 45.5 46.1

Shims 0mm

Line In Line Out

Washers 2mm

Shims 0mm

Cap Type Vented Sealed Emulsion

Oil.....cTs

Spring.....

Piston.....

Drilled Yes No

Drilled piston Hole Size.....mm

Shock Length (X).....mm

Rebound%

Peripheral Damping Yes No