

### DRIVER DETAILS

NAME makoto oda  
 DATE 2011/8/25/26  
 EVENT JMRCA Sportsclass  
 WEATHER  
 RESULT 4th  
 FASTEST LAP TIME

### NOTES

U4610x2 USE  
 U4807 USE



### CHASSIS AND ELECTRICS

CHASSIS Alloy  Carbon   
 TOP DECK 2.0mm  2.5mm  3.0mm  4.0mm   
 BODYSHELL ALEX M6 highspeed  
 WING rc mission  
 E.S.C HOBBYWING XR-10  
 SERVO SANWA P65-LH  
 RECEIVER SANWA RX-482  
 CELLS

### MOTOR AND GEARING

MOTOR R1 WURKS  
 ROTOR DIAMETER 12.5MM  
 TIMING 0  
 GEAR PITCH 48DP  64DP   
 SPUR SIZE 106  
 PINION SIZE 35

### TRACK CONDITIONS

GRIP LEVEL High  Medium  Low   
 TYPE Tight  Open  Mixed   
 SURFACE Carpet  Tarmac   
 CONDITION Smooth  Bumpy   
 TEMPERATURE °C °F  
 VENUE Indoor  Outdoor

### WHEELS, TYRES AND INSERTS

WHEELS YOKOMO(control)  
 TYRES SORTEX40(control)  
 INSERTS bomber red(control)  
 TYRE ADDITIVE mighty3(control)  
 ADDITIVE TIME Front 1 Minutes Rear 1 Minutes  
 TYRE WARMERS Yes  No  Temp 40 °C Time 1 Minutes

### FRONT

Diff Oil ..... cTs

Spool  
 Gear Diff

1 Dot - 1.1mm  
 2 Dot - 1.2mm  
 3 Dot - 1.3mm  
 4 Dot - 1.4mm  
 5 Dot - 1.5mm

Line In  Shims 0 .....mm  
 Line Out  0 .....mm

Drop.....mm  
 On 10mm Block   
 Ride Height 4.4 .....mm  
 Camber 2 .....°  
 Toe.....OUT 1 .....°  
 Pivot Block Strap

43.5  44.2  46.0

Washers 2 .....mm  
 Washers.....3 .....mm

Washers 0.5 .....mm

4° Yoke   
 6° Yoke

SERVO SAVER Yes  No

Washers 2 .....mm

12mm   
 13mm   
 14mm

Alloy  Steel  Double Joint

Narrow   
 Medium (kit)

Washers 1 .....mm

Cap Type Vented  Sealed  Emulsion   
 Oil..... AXDN71.5 .....cTs  
 Spring..... AXDN2.5 .....  
 Piston..... NORMAL .....  
 Drilled Yes  No   
 Drilled piston Hole Size.....mm  
 Shock Length (X).....mm  
 Rebound .....%

Peripheral Damping Yes  No

### REAR

Diff Oil 1000 ..... cTs

0 Dot - 1.0mm  
 1 Dot - 1.1mm  
 2 Dot - 1.2mm  
 3 Dot - 1.3mm  
 4 Dot - 1.4mm

Medium   
 Wide (kit)

Drop.....mm  
 On 10mm Block   
 Ride Height 4.6 .....mm  
 Camber 2 .....°  
 Pivot Block Strap

44.2  45.5  46.1

Washers 2 .....mm

Washers 1 .....mm

WheelBase Short  Middle  Long

Alloy  Steel

Washers 2 .....mm

Shims 0 .....mm

Cap Type Vented  Sealed  Emulsion   
 Oil..... AXDN71.5 .....cTs  
 Spring..... AXDN2.5 .....  
 Piston..... NORMAL .....  
 Drilled Yes  No   
 Drilled piston Hole Size.....mm  
 Shock Length (X).....mm  
 Rebound .....%

Peripheral Damping Yes  No