

DRIVER DETAILS

NAME **Robert Krens**
 DATE **04-02-2018**
 EVENT **MRC - CW#4**
 WEATHER **-**
 RESULT **TQ + Win**
 FASTEST LAP TIME **FL: 9.530** **34L in 6:10438**

NOTES

TOP DECK CONNECTOR YES NO
Car is great, Morning run with VGMeuk V1 (more aggressive feel, more "side bite" grip feel) Second run with VGMeuk V2
Drop measured above ride height
Weight in all for corners of the car (front of servo, front of battery, rear of battery, rear of motor) 28gr in total)



Alterations by Arn0 - PetitRC.com

CHASSIS AND ELECTRICS

CHASSIS Alloy Carbon
 TOP DECK 2.0mm 2.5mm 3.0mm 4.0mm
 BODYSHELL **Montech Racer - 0mm forward - 89gram**
 WING **STD - 10mm past the rear end (EFRA)**
 E.S.C **Much More Fleta Euro**
 SERVO **Futaba 9551**
 RECEIVER **Sanwa 451R**
 CELLS **Basher LiHV - 5600mah 90C**

MOTOR AND GEARING

MOTOR **"Hand-out" Turnigy 17,5T**
 ROTOR DIAMETER **STD**
 TIMING **Last Dot**
 GEAR PITCH 48DP 64DP
 SPUR SIZE **96**
 PINION SIZE **43**

TRACK CONDITIONS

GRIP LEVEL High Medium Low
 TYPE Tight Open Mixed
 SURFACE Carpet Tarmac
 CONDITION Smooth Bumpy
 TEMPERATURE **21 °C** °F
 VENUE Indoor Outdoor

WHEELS, TYRES AND INSERTS

WHEELS **Sorex 28**
 TYRES
 INSERTS
 TYRE ADDITIVE **VGMeuk V2**
 ADDITIVE TIME Front **15 Minutes** Rear **15 Minutes**
 TYRE WARMERS Yes No Temp °C Time Minutes

FRONT

Spool
 Gear Diff

Diff Oil cTs

1 Dot - 1.1mm
 2 Dot - 1.2mm
 3 Dot - 1.3mm
 4 Dot - 1.4mm
 5 Dot - 1.5mm

Drop **1.5** mm
 On 10mm Block
 Ride Height **5.8** mm
 Camber..... **2.0** °
 Toe..... **1.0** °
 Pivot Block Strap

Washers **1.5** mm
 Washers..... **1.5** mm

Washers **0.5** mm

Line In
Line Out

Shims **0.5** mm

Shims..... **0** mm

4° R 4° Yoke
 6° Yoke

SERVO SAVER
Yes
No

Washers **2.0** mm

12mm
13mm
14mm

Alloy Steel Double Joint

Narrow
 Medium (kit)

Washers **1.0** mm

Cap Type Vented Sealed Emulsion
 Oil..... **500** cTs
 Spring..... **Yoko Pink**
 Piston..... **#3**
 Drilled Yes No
 Drilled piston Hole Size..... **1.1** mm
 Shock Length (X)..... **9.57** mm
 Rebound **0** %

Peripheral Damping
Yes
No

REAR

Diff Oil **3000** cTs

Drop..... **2.5** mm
 On 10mm Block
 Ride Height **6.0** mm
 Camber..... **2.2** °
 Pivot Block Strap

0 Dot - 1.0mm
 1 Dot - 1.1mm
 2 Dot - 1.2mm
 3 Dot - 1.3mm
 4 Dot - 1.4mm

(2 Pip shown)
 0 Groove
 1 Groove
 2 Groove

Washers **0.5** mm

Washers **1.5** mm

Shims..... **0.5** mm

Shims..... **0.5** mm

Alloy Steel

WheelBase
 Short
 Middle
 Long

Cap Type Vented Sealed Emulsion
 Oil..... **500** cTs
 Spring..... **Yoko Blue**
 Piston..... **#3**
 Drilled Yes No
 Drilled piston Hole Size..... **1.1** mm
 Shock Length (X)..... **9.57** mm
 Rebound **0** %

Peripheral Damping
Yes
No