

DRIVER DETAILS

NAME _____

DATE _____

EVENT _____

WEATHER _____

RESULT _____

FASTEST LAP TIME _____

NOTES



CHASSIS AND ELECTRICS

CHASSIS Alloy Carbon

TOP DECK 2.0mm 2.5mm 3.0mm 4.0mm

BODYSHELL _____

WING _____

E.S.C _____

SERVO _____

RECEIVER _____

CELLS _____

MOTOR AND GEARING

MOTOR _____

ROTOR DIAMETER _____

TIMING _____

GEAR PITCH 48DP 64DP

SPUR SIZE _____

PINION SIZE _____

TRACK CONDITIONS

GRIP LEVEL High Medium Low

TYPE Tight Open Mixed

SURFACE Carpet Tarmac

CONDITION Smooth Bumpy

TEMPERATURE _____ °C _____ °F

VENUE Indoor Outdoor

WHEELS, TYRES AND INSERTS

WHEELS _____

TYRES _____

INSERTS _____

TYRE ADDITIVE _____

ADDITIVE TIME Front Minutes Rear Minutes

TYRE WARMERS Yes No Temp °C Time Minutes

FRONT

Spool
 Gear Diff

Diff Oil cTs

1 Dot - 1.1mm
 2 Dot - 1.2mm
 3 Dot - 1.3mm
 4 Dot - 1.4mm
 5 Dot - 1.5mm

Line In
Line Out

Droop.....mm
On 10mm Block
Ride Heightmm
Camber.....°
Toe.....°
Pivot Block Strap

44.2
43.5 44.2 46.0

Washersmm

Washersmm

Washersmm

Washersmm

12mm
13mm
14mm

Cap Type Vented Sealed Emulsion
Oil.....cTs
Spring.....
Piston.....
Drilled Yes No
Drilled piston Hole Size.....mm
Shock Length (X).....mm
Rebound%

Peripheral Damping Yes No

Alloy Steel Double Joint

Narrow
Medium (kit)

Washersmm

REAR

Diff Oil cTs

0 Dot - 1.0mm
 1 Dot - 1.1mm
 2 Dot - 1.2mm
 3 Dot - 1.3mm
 4 Dot - 1.4mm

Medium
 Wide (kit)

(2 Pip shown)
 0 Groove
 1 Groove
 2 Groove

Droop.....mm
On 10mm Block
Ride Heightmm
Camber.....°
Pivot Block Strap

48.1
44.2 45.5 46.1

Washersmm

Washersmm

Washersmm

WheelBase
 Short
 Middle
 Long

Alloy Steel

Washersmm