

DRIVER DETAILS

NAME
DATE
EVENT
WEATHER
RESULT
FASTEST LAP TIME

NOTES



CHASSIS AND ELECTRICS

CHASSIS Alloy Carbon
TOP DECK 2.0mm 2.5mm 3.0mm 4.0mm
BODYSHELL
WING
E.S.C
SERVO
RECEIVER
CELLS

MOTOR AND GEARING

MOTOR
ROTOR DIAMETER
TIMING
GEAR PITCH 48DP 64DP
SPUR SIZE
PINION SIZE

TRACK CONDITIONS

GRIP LEVEL High Medium Low
TYPE Tight Open Mixed
SURFACE Carpet Tarmac
CONDITION Smooth Bumpy
TEMPERATURE °C °F
VENUE Indoor Outdoor

WHEELS, TYRES AND INSERTS

WHEELS
TYRES
INSERTS
TYRE ADDITIVE
ADDITIVE TIME Front Minutes Rear Minutes
TYRE WARMERS Yes No Temp °C Time Minutes

FRONT

FRONT assembly diagrams including: Diff Oil (Spool, Gear Diff), Washers, Servo Saver (4°/6° Yoke), Alloy/Steel/Double Joint, Narrow/Medium/Wide kit, Shims, Line In/Out, Shims, Diff Oil (Vented/Sealed/Emulsion), Spring, Piston, Drilled piston Hole Size, Shock Length (X), Rebound, Peripheral Damping, and various adjustment points like Droop, On 10mm Block, Ride Height, Camber, Toe, and Pivot Block Strap.

REAR

REAR assembly diagrams including: Diff Oil, Washers, WheelBase (Short/Middle/Long), Alloy/Steel, Shims, Line In/Out, Diff Oil (Vented/Sealed/Emulsion), Spring, Piston, Drilled piston Hole Size, Shock Length (X), Rebound, Peripheral Damping, and various adjustment points like Droop, On 10mm Block, Ride Height, Camber, and Pivot Block Strap.