

### DRIVER DETAILS

NAME **Larry Myers**  
 DATE **6-12-16**  
 EVENT **Eos**  
 WEATHER **Hot**  
 RESULT  
 FASTEST LAP TIME

### NOTES

**Jet Hoppys aluminum front steering .5 mm shim between chassis and steering rack no bump steer shim**



Alterations by Am0

### CHASSIS AND ELECTRICS

CHASSIS Alloy  Carbon   
 TOP DECK 2.0mm  2.5mm  3.0mm  4.0mm   
 BODYSHELL **R9r**  
 WING **Top line**  
 E.S.C **R10 pro**  
 SERVO **Savox 1258**  
 RECEIVER **Fut**  
 CELLS **Protek 7800 90c 318g**

### MOTOR AND GEARING

MOTOR **Hacker 6.5**  
 ROTOR DIAMETER **Stock**  
 TIMING **30**  
 GEAR PITCH 48DP  64DP   
 SPUR SIZE **110**  
 PINION SIZE **37**

### TRACK CONDITIONS

GRIP LEVEL High  Medium  Low   
 TYPE Tight  Open  Mixed   
 SURFACE Carpet  Tarmac   
 CONDITION Smooth  Bumpy   
 TEMPERATURE °C °F **90**  
 VENUE Indoor  Outdoor

### WHEELS, TYRES AND INSERTS

WHEELS **Spec**  
 TYRES **Sweep 36**  
 INSERTS **Spec**  
 TYRE ADDITIVE **White can paragon**  
 ADDITIVE TIME Front **30sec** Minutes Rear **30sec** Minutes  
 TYRE WARMERS Yes  No  Temp °C Time Minutes

### FRONT

Spool  
 Gear Diff

Diff Oil ..... cTs

1 Dot - 1.1mm  
 2 Dot - 1.2mm  
 3 Dot - 1.3mm  
 4 Dot - 1.4mm  
 5 Dot - 1.5mm

Line In   
Line Out

Drop... **1.5** .....mm  
 On 10mm Block   
 Ride Height ..... **5.5** .....mm  
 Camber..... **2.1** °  
 Toe..... **+1.0** °  
 Pivot Block Strap

Washers ..... **1.0** .....mm  
 Shims ..... **0** .....mm

44.2  44.2  46.0

Washers ..... **1.0** .....mm

Washers ..... **0** .....mm

Washers ..... **5** .....mm

12mm   
13mm   
14mm

Cap Type Vented  Sealed  Emulsion   
 Oil..... **400** .....cTs  
 Spring... **Yokomo pink** .....  
 Piston... **Kit** .....  
 Drilled Yes  No   
 Drilled piston Hole Size.....mm  
 Shock Length (X)..... **10** .....mm  
 Rebound ..... **0** %

Peripheral Damping Yes  No

Alloy  Steel  Double Joint

Narrow  Medium (kit)

Washers ..... **1.0** .....mm

### REAR

Diff Oil **2000** ..... cTs

Drop..... **3.0** .....mm  
 On 10mm Block   
 Ride Height ..... **6.0** .....mm  
 Camber..... **2.2** °  
 Pivot Block Strap

Line In   
Line Out

0 Dot - 1.0mm  
 1 Dot - 1.1mm  
 2 Dot - 1.2mm  
 3 Dot - 1.3mm  
 4 Dot - 1.4mm

Washers ..... **1.0** .....mm

WheelBase  Short  Middle  Long

Washers ..... **1.0** .....mm

Washers ..... **0** .....mm

Washers ..... **1.0** .....mm

Shims..... **0.5** .....mm

Shims..... **0.5** .....mm

Cap Type Vented  Sealed  Emulsion   
 Oil..... **400** .....cTs  
 Spring... **Yokomo pink** .....  
 Piston... **Kit** .....  
 Drilled Yes  No   
 Drilled piston Hole Size.....mm  
 Shock Length (X)..... **10** .....mm  
 Rebound ..... **0** %

Peripheral Damping Yes  No

Alloy  Steel

Medium  Wide (kit)