

DRIVER DETAILS

NAME Larry Myers
 DATE
 EVENT HobbyTown USA south store
 WEATHER Sunny
 RESULT P2 Second place
 FASTEST LAP TIME 11.9

NOTES

Jet hobbies aluminum front steering knuckles
 loose rear belt front belt a little on the tight side
 both top deck braces installed no bump steer
 shams .5 mm washer between chassis and
 steering rack



CHASSIS AND ELECTRICS

CHASSIS Alloy Carbon
 TOP DECK 2.0mm 2.5mm 3.0mm 4.0mm
 BODYSHELL R4r
 WING Cut on lower line
 E.S.C Orion r10 pro
 SERVO Savox 1258
 RECEIVER Fut
 CELLS Protek 7800 90c 318g

MOTOR AND GEARING

MOTOR Phantom certified 17.5 D4 short stack
 ROTOR DIAMETER 12.5
 TIMING 51
 GEAR PITCH 48DP 64DP
 SPUR SIZE 16
 PINION SIZE 42

TRACK CONDITIONS

GRIP LEVEL High Medium Low
 TYPE Tight Open Mixed
 SURFACE Carpet Tarmac
 CONDITION Smooth Bumpy
 TEMPERATURE °C 10 °F
 VENUE Indoor Outdoor

WHEELS, TYRES AND INSERTS

WHEELS Sweep 36 EVO
 TYRES 5pc
 INSERTS 5pc
 TYRE ADDITIVE White can paragon
 ADDITIVE TIME Front 30 sec Minutes Rear 30sec Minutes
 TYRE WARMERS Yes No Temp °C Time Minutes

FRONT

Diff Oil cTs

Spool
 Gear Diff

1 Dot - 1.1mm
 2 Dot - 1.2mm
 3 Dot - 1.3mm
 4 Dot - 1.4mm
 5 Dot - 1.5mm

Dropo... 1.5mm
 On 10mm Block
 Ride Height... 5.5mm
 Camber... 2.1°
 Toe... 1.0°
 Pivot Block Strap

4° R 6° Yoke
 SERVO SAVER Yes No

Washers 1.0mm
 Washers 1.0mm

Washers 5mm
 12mm
 13mm
 14mm

Cap Type Vented Sealed Emulsion
 Oil... 425ctscTs
 Spring... Yok Pink
 Piston... Kit
 Drilled Yes No
 Drilled piston Hole Size... Kitmm
 Shock Length (X)... 10.0mm
 Rebound 0%

Peripheral Damping Yes No

Alloy Steel Double Joint

Narrow Medium (kit)

Washers 2.0mm

Line In Shims 0mm
 Line Out Shims 0mm

REAR

Diff Oil 1200 cTs

1.0mm
 1.0mm

Medium Wide (kit)

Dropo... 3.5mm
 On 10mm Block
 Ride Height... 6.0mm
 Camber... 2.0°
 Pivot Block Strap

0 Dot - 1.0mm
 1 Dot - 1.1mm
 2 Dot - 1.2mm
 3 Dot - 1.3mm
 4 Dot - 1.4mm

(2 Pip shown)
 0 Groove
 1 Groove
 2 Groove

Washers 1.0mm
 WheelBase Short Middle Long

Washers 1mm

Alloy Steel

Washers 0mm

Line In Shims 0mm
 Line Out Shims 5mm

Cap Type Vented Sealed Emulsion
 Oil... 400ctscTs
 Spring... Yok Orange
 Piston... Kit
 Drilled Yes No
 Drilled piston Hole Size... Kitmm
 Shock Length (X)... 10mm
 Rebound 0%

Peripheral Damping Yes No