

DRIVER DETAILS

NAME _____

DATE _____

EVENT _____

WEATHER _____

RESULT _____

FASTEST LAP TIME _____

NOTES



CHASSIS AND ELECTRICS

CHASSIS Alloy Carbon

TOP DECK 2.0mm 2.5mm 3.0mm 4.0mm

BODYSHELL _____

WING _____

E.S.C _____

SERVO _____

RECEIVER _____

CELLS _____

MOTOR AND GEARING

MOTOR _____

ROTOR DIAMETER _____

TIMING _____

GEAR PITCH 48DP 64DP

SPUR SIZE _____

PINION SIZE _____

TRACK CONDITIONS

GRIP LEVEL High Medium Low

TYPE Tight Open Mixed

SURFACE Carpet Tarmac

CONDITION Smooth Bumpy

TEMPERATURE _____ °C _____ °F

VENUE Indoor Outdoor

WHEELS, TYRES AND INSERTS

WHEELS _____

TYRES _____

INSERTS _____

TYRE ADDITIVE _____

ADDITIVE TIME	Front	Minutes	Rear	Minutes
TYRE WARMERS	Yes <input type="checkbox"/>	No <input type="checkbox"/>	Temp °C	Time Minutes

FRONT

Spool
 Gear Diff

Diff Oil cTs

1 Dot - 1.1mm
 2 Dot - 1.2mm
 3 Dot - 1.3mm
 4 Dot - 1.4mm
 5 Dot - 1.5mm

Washersmm

Line In
Line Out

Shimsmm

Droop.....mm
On 10mm Block
Ride Heightmm
Camber.....°
Toe.....°
Pivot Block Strap

44.2 46.0

Washersmm

4° Yoke
 6° Yoke

Yes
No

SERVO SAVER

Washersmm

12mm
13mm
14mm

Cap Type Vented Sealed Emulsion

Oil.....cTs

Spring.....

Piston.....

Drilled Yes No

Drilled piston Hole Size.....mm

Shock Length (X).....mm

Rebound%

Peripheral Damping
Yes
No

Alloy Steel Double Joint

Narrow
 Medium (kit)

Washersmm

REAR

Diff Oil cTs

Washersmm

0 Dot - 1.0mm
 1 Dot - 1.1mm
 2 Dot - 1.2mm
 3 Dot - 1.3mm
 4 Dot - 1.4mm

(2 Pip shown)

0 Groove
 1 Groove
 2 Groove

Washersmm

WheelBase
 Short
 Middle
 Long

Line In
Line Out

Shimsmm

Droop.....mm
On 10mm Block
Ride Heightmm
Camber.....°
Pivot Block Strap

44.2 46.1

Washersmm

Cap Type Vented Sealed Emulsion

Oil.....cTs

Spring.....

Piston.....

Drilled Yes No

Drilled piston Hole Size.....mm

Shock Length (X).....mm

Rebound%

Peripheral Damping
Yes
No

Alloy Steel