

### DRIVER DETAILS

NAME Phil V - dRC.com  
 DATE  
 EVENT Starting set up Black Carpet  
 WEATHER  
 RESULT  
 FASTEST LAP TIME

### NOTES

Blue front tires to top of Jaco  
 5 mm shim under steering block (U4256)  
 Both Top Deck Braces



### CHASSIS AND ELECTRICS

CHASSIS Alloy  Carbon   
 TOP DECK 2.0mm  2.5mm  3.0mm  4.0mm   
 BODYSHELL Nazda 2 - 79.5mm from bottom window line  
 WING Stock - 10mm overhang  
 E.S.C HW XR10  
 SERVO Ko response RSX one10  
 RECEIVER 42014  
 CELLS Fantom LCG 6000

### MOTOR AND GEARING

MOTOR HW 4.5  
 ROTOR DIAMETER Stock  
 TIMING 10°  
 GEAR PITCH 48DP  64DP   
 SPUR SIZE 118  
 PINION SIZE 30T

### TRACK CONDITIONS

GRIP LEVEL High  Medium  Low   
 TYPE Tight  Open  Mixed   
 SURFACE Carpet  Tarmac   
 CONDITION Smooth  Bumpy   
 TEMPERATURE °C °F  
 VENUE Indoor  Outdoor

### WHEELS, TYRES AND INSERTS

WHEELS Jaco blue handouts  
 TYRES  
 INSERTS  
 TYRE ADDITIVE SXT or LGC  
 ADDITIVE TIME Front Full 6 Minutes Rear Full 6 Minutes  
 TYRE WARMERS Yes  No  Temp °C Time Minutes

### FRONT

Diff Oil ..... cTs

Spool  
 Gear Diff

1 Dot - 1.1mm  
 2 Dot - 1.2mm  
 3 Dot - 1.3mm  
 4 Dot - 1.4mm  
 5 Dot - 1.5mm

Washers 2 .....mm  
 Washers ..... 0mm

Shims 0 .....mm

Line In   
 Line Out

Drop 2.0rh .....mm  
 On 10mm Block   
 Ride Height 5.3 .....mm  
 Camber 2 .....°  
 Toe 1.5 .....°  
 Pivot Block Strap

Washers 2 .....mm

Shims 0 .....mm

Cap Type Vented  Sealed  Emulsion   
 Oil 450 .....cTs  
 Spring Yok Pink  
 Piston 4 hole  
 Drilled Yes  No   
 Drilled piston Hole Size 1.1 .....mm  
 Shock Length (X) 10.00 .....mm  
 Rebound 10 .....%

Peripheral Damping  
 Yes   
 No

4° R  6° Yoke  
 SERVO SAVER Yes  No

Washers 2 .....mm  
 12mm   
 13mm   
 14mm

Alloy  Steel  Double Joint

Narrow   
 Medium (kit)   
 Washers 1 .....mm

### REAR

Diff Oil 3000 ..... cTs

1.3 .....mm  
 1.3 .....mm

Washers 2 .....mm

Shims 5 .....mm

Line In   
 Line Out

Drop 2.5 rh .....mm  
 On 10mm Block   
 Ride Height 5.3 .....mm  
 Camber 2 .....°  
 Pivot Block Strap

Washers 5 .....mm

Shims 5 .....mm

Cap Type Vented  Sealed  Emulsion   
 Oil 450 .....cTs  
 Spring Yok Blue  
 Piston 4 hole  
 Drilled Yes  No   
 Drilled piston Hole Size 1.1 .....mm  
 Shock Length (X) 10 .....mm  
 Rebound 10 .....%

Peripheral Damping  
 Yes   
 No

0 Groove   
 1 Groove   
 2 Groove  (2 Pip shown)

WheelBase Short  Middle  Long

Alloy  Steel

Narrow   
 Medium  Wide (kit)