

### DRIVER DETAILS

NAME RICH  
 DATE  
 EVENT RPON  
 WEATHER 80° EVENING UNDER LIGHTS  
 RESULT 3RD  
 FASTEST LAP TIME 13.9

### NOTES

USE .5 MM SHIM BETWEEN STEERING BLOCK AND CONE WASHER (UP584)

BOTH BRACES IN TOP DECK

U4108 AND U4135 STRAPS IN FRONT



### CHASSIS AND ELECTRICS

CHASSIS Alloy  Carbon   
 TOP DECK 2.0mm  2.5mm  3.0mm  4.0mm   
 BODYSHELL SPEED 6  
 WING STOCK  
 E.S.C HOBBY WING  
 SERVO  
 RECEIVER  
 CELLS

### MOTOR AND GEARING

MOTOR TEAM POWERS 17.5  
 ROTOR DIAMETER STOCK  
 TIMING MAX  
 GEAR PITCH 48DP  64DP   
 SPUR SIZE 96  
 PINION SIZE 3.8 fdr

### TRACK CONDITIONS

GRIP LEVEL High  Medium  Low   
 TYPE Tight  Open  Mixed   
 SURFACE Carpet  Tarmac   
 CONDITION Smooth  Bumpy   
 TEMPERATURE °C °F  
 VENUE Indoor  Outdoor

### WHEELS, TYRES AND INSERTS

WHEELS  
 TYRES  
 INSERTS  
 TYRE ADDITIVE  
 ADDITIVE TIME Front Minutes Rear Minutes  
 TYRE WARMERS Yes  No  Temp °C Time Minutes

### FRONT

Diff Oil ..... cTs

Spool  
 Gear Diff

1 Dot - 1.1mm  
 2 Dot - 1.2mm  
 3 Dot - 1.3mm  
 4 Dot - 1.4mm  
 5 Dot - 1.5mm

Line In  Shims 0 .....mm  
 Line Out  Shims 0 .....mm

Washers 1 .....mm  
 Washers ..... 0mm

Washers 0 .....mm

Washers 1.5 .....mm

12mm   
 13mm   
 14mm

Droop .5 .....mm  
 On 10mm Block   
 Ride Height .52 .....mm  
 Camber .15 .....°  
 Toe .25 .....°  
 Pivot Block Strap

43.5  44.2  46.0

4° R  4° Yoke  6° Yoke   
 SERVO SAVER Yes  No

Alloy  Steel  Double Joint

Narrow  Medium (kit)

Washers 1 .....mm

Cap Type Vented  Sealed  Emulsion   
 Oil .450 .....cTs  
 Spring GREEN  
 Piston STOCK  
 Drilled Yes  No   
 Drilled piston Hole Size .11 .....mm  
 Shock Length (X) 1.75 .....mm  
 Rebound 10 .....%

Peripheral Damping Yes  No

### REAR

Diff Oil 3000 ..... cTs

0 Dot - 1.0mm  
 1 Dot - 1.1mm  
 2 Dot - 1.2mm  
 3 Dot - 1.3mm  
 4 Dot - 1.4mm

Washers .5 .....mm

WheelBase Short  Middle  Long

Medium  Wide (kit)

(2 Pip shown)

0 Groove  1 Groove  2 Grooves

Washers 0 .....mm

Droop .4 .....mm  
 On 10mm Block   
 Ride Height .55 .....mm  
 Camber .2 .....°  
 Pivot Block Strap

44.2  45.5  46.1

Shims 5 .....mm Shims .5 .....mm

Alloy  Steel

Cap Type Vented  Sealed  Emulsion   
 Oil .450 .....cTs  
 Spring GREEN  
 Piston STOCK  
 Drilled Yes  No   
 Drilled piston Hole Size .11 .....mm  
 Shock Length (X) 1.75 .....mm  
 Rebound 10 .....%

Peripheral Damping Yes  No