Driver: John Simpson Date: 15 july Meeting: carlisle cup round 2 Best Time: Quali 2 Ride Height^{5.5} Dil....35wt OOO Anti-Roll Bar..... Spring Sch White **0**6° **O**4° Piston....2.4.3.... Kick Up.....Anti-Dive......MM Length...62 mm. Toe-In/Out -1 degrees Droop....4.5 MM. Fill holes used Roll Centre Riser + 1 mm Camber -1 degrees Centre Track Wishbone Short Mid/Short Mid/Long OLong All gearbox risers removed and Fill holes used USA carpet towers used. 0 Second hole in from outside ● Carbon ○ Standard ○ Standard ● Carpet □il 35wt Anti-Roll Bar. silver 000 Spring Sch White Anti/Pro Squat... Piston....2....3.... Toe-In (In) std degrees Length...61 mm 0 Roll Centre Riser + 1 mm Fill holes used Camber -2 degrees Fill holes used Wishbone Short Mid/Short Mid/Long OLong **OP** Spacer*mm* \bigcirc 0 All gearbox risers removed ● Carbon ○ Standard and USA carpet towers used. Second hole in from outside Width Front std mm Rear std mm Bodyshell Mazda speed 6 Olndoor Motor Checkpoint 9x1 OStandard OLocked One-Way Z ⊙ Outdoor Differential..... Brush...infinity Chassis ... Std EC 2mm Spring medium hard Top Deck Std EC 2mm **Carpet** Timing 1 notch degrees **O**Concrete E.S.C. Nosram **≌ ⊙**Tarmac Pinion Size.....¹⁹ tooth Cells Orion S O..... Spur Size.....⁸⁹ tooth Servo. KO Receiver .KO 置●Tight と○Open Car was good it held good Front Tyres RP30 preglue **OHigh** corner speed and was 돌 • Wedium Rear Tyres. RP30 preglue easy to drive. OLow Front Inserts..... Rear Inserts..... **●** Smooth **O Bumpy**