

## DRIVER AND EVENT DETAILS

Name   
 Date   
 Event   
 Weather   
 Result

## CHASSIS AND ELECTRICS

Chassis   
 Top Deck   
 Bodyshell   
 Wing   
 E.S.C   
 Servo   
 Receiver   
 Cells

## TRACK CONDITIONS

Grip Level  High  Medium  Low   
 Type  Tight  Open  Both   
 Surface  Carpet  Tarmac  Wood   
 Condition  Smooth  Bumpy   
 Temperature  °C  °F  
 Venue  Indoor  Outdoor



## MOTOR AND GEARING

Motor   
 Rotor Diameter   
 Timing   
 Gear Pitch  48Dp  64Dp   
 Spur Size   
 Pinion Size

## Transmission

Option 1  Option 2

## WHEELS, TYRES AND INSERTS

Wheels   
 Tyres   
 Inserts   
 Tyre Additive   
 Additive Time   
 Tyre Warmers  Yes  No

## DRIVER NOTES

Long rear arms (original Mi4 kit)

## Front Shocks

Oil   
 Springs   
 Piston Holes  2  3   
 length   
 Rebound

## FRONT SETTINGS

Drive  Diff  Spool  One-Way  Height  High  Low

Servo Saver  Yes  No  Yoke Flex  X  M  STD

Pivot Blocks   Alloy

Screw Block Spacers  mm  mm

Wishbone Quik-Klips  mm  mm

Toe In-Out  In-board  Out-board   °

Ride Height (Chassis to Floor)  mm

Droop  On 10mm Block  Axle Height   mm

Anti-roll Bar  No   1.20  1.40  1.60


Castor  0°  2°  4°  6°

Camber  Positive  Negative   Deg




Link Washers  Under Ball  Under Bracket   mm

Inboard Pin  Kick-up  Anti-dive  Horizontal

Pivot Block Spacers  mm  mm



Wishbone Flex  CF  M



## Centre Track Rod

Washers  mm

## Link Mount

1 Groove - 45mm   
 2 Groove - 42mm   
 3 Groove - 39mm   
 4 Groove - 37mm

## REAR SETTINGS

Drive Height  High  Low

Pivot Blocks   Alloy

Screw Block Spacers  mm  mm

Wishbone Quik-Klips  mm  mm

Toe In  In-board  3.5°  Out-board  °

Ride Height (Chassis to Floor)  mm

Droop  On 10mm Block  Axle Height   mm


Anti-roll Bar  No   1.20  1.40  1.60

Camber  Positive  Negative   Deg


Link Washers  Under Ball  Under Bracket   mm

Inboard Pin  Pro-Squat  Anti-Squat  Horizontal

Pivot Block Spacers  mm  mm




Wishbone Flex  CF  M



## Link Mount

1 Groove - 45mm   
 2 Groove - 42mm   
 3 Groove - 39mm   
 4 Groove - 37mm



## Rear Shocks

Oil   
 Springs   
 Piston Holes  2  3   
 length   
 Rebound