

### DRIVER AND EVENT DETAILS

Name *Martin Hofer*  
 Date *18.-20.3.2011*  
 Event *ETS Rd4 Warsaw*  
 Weather *grey*  
 Result *WIN*

### CHASSIS AND ELECTRICS

Chassis *2mm*  
 Top Deck *2mm*  
 Bodyshell *Speed 6 LW*  
 Wing *std*  
 E.S.C *SP Citrix*  
 Servo *Sanwa 801*  
 Receiver *Sanwa 451*  
 Cells *GM V-Maxx*

### TRACK CONDITIONS

Grip Level High  Medium  Low   
 Type Tight  Open  Both   
 Surface Carpet  Tarmac  Wood   
 Condition Smooth  Bumpy   
 Temperature *20* °C °F  
 Venue Indoor  Outdoor



### WHEELS, TYRES AND INSERTS

Wheels *JB xhard robotronic*  
 Tyres *xenon*  
 Inserts *jrp blue*  
 Tyre Additive *LRP*  
 Additive Time *20 MIN (R) 20 MIN (F)*  
 Tyre Warmers Yes  No

### MOTOR AND GEARING

Motor *SP*  
 Rotor Diameter *efra*  
 Timing *fixed*  
 Gear Pitch 48Dp  64Dp   
 Spur Size *90*  
 Pinion Size *36*

### Transmission

Option 1  Option 2

### DRIVER NOTES

*narrow front hexes, 0.5 against rear hex, TP steering, 2nd hole from back,*


### Front Shocks

Oil *50 WT*  
 Springs *HPI Gold*  
 Piston Holes 2  3   
 length *12,6*  
 Rebound *20%*




### FRONT SETTINGS

Drive Diff  Spool  One-Way  Height High  Low

Servo Saver Yes  No  Yoke Flex X  M  STD   
 Pivot Blocks Moulded (std)  Alloy   
 Screw Block Spacers Front *2.5 mm* Rear *2.5 mm*  
 Wishbone Quik-Klips Front *2.5 mm* Rear *1.5 mm*  
 Toe In-Out In-board  Out-board  *0.3* °  
 Ride Height (Chassis to Floor) *5.0 mm*  
 Droop On 10mm Block  Axle Height  *5 mm*  
 Anti-roll Bar No  1.20  1.40  1.60   
 Castor 0°  2°  4°  6°   
 Camber Positive  Negative  *1,5 Deg*  
 Link Washers Under Ball  Under Bracket  *2 mm*  
 Inboard Pin Kick-up  Anti-dive  Horizontal   
 Pivot Block Spacers Front *1.8 mm* Rear *1.5 mm*



Wishbone Flex CF  M



### Centre Track Rod

Washers *mm*


### Link Mount

1 Groove - 45mm   
 2 Groove - 42mm   
 3 Groove - 39mm   
 4 Groove - 37mm


### REAR SETTINGS

Drive Height High  Low

Pivot Blocks Moulded (std)  Alloy   
 Screw Block Spacers Front *1.5 mm* Rear *0.5 mm*  
 Wishbone Quik-Klips Front *2 mm* Rear *2 mm*  
 Toe In In-board  *3* ° Out-board  °  
 Ride Height (Chassis to Floor) *5.2 mm*  
 Droop On 10mm Block  Axle Height  *4.2 mm*  
 Anti-roll Bar No  1.20  1.40  1.60   
 Camber Positive  Negative  *2 Deg*  
 Link Washers Under Ball  Under Bracket  *0 mm*  
 Inboard Pin Pro-Squat  Anti-Squat  Horizontal   
 Pivot Block Spacers Front *2.5 mm* Rear *mm*





Wishbone Flex CF  M



### Link Mount

1 Groove - 45mm   
 2 Groove - 42mm   
 3 Groove - 39mm   
 4 Groove - 37mm



### Rear Shocks

Oil *50 WT*  
 Springs *HPI Silver*  
 Piston Holes 2  3   
 length *12,6*  
 Rebound *20%*