

## DRIVER AND EVENT DETAILS

Name Paul Pinkney  
 Date 27/11/2011  
 Event EWS  
 Weather Fine and Dry  
 Result TQ & Win

## CHASSIS AND ELECTRICS

Chassis 2.0 Soft Weave  
 Top Deck Long Asphalt  
 Bodyshell Mazda Speed 6 LW  
 Wing HPI 190  
 E.S.C SP GT2.0 Pro  
 Servo Futaba 9551  
 Receiver Sanwa 451R  
 Cells Demon Shorty Lipo

## TRACK CONDITIONS

Grip Level High  Medium  Low   
 Type Tight  Open  Both   
 Surface Carpet  Tarmac  Wood   
 Condition Smooth  Bumpy   
 Temperature 18 °C °F  
 Venue Indoor  Outdoor

## MOTOR AND GEARING

Motor SP 13.5mm  
 Rotor Diameter 12.5 black  
 Timing std  
 Gear Pitch 48Dp  64Dp   
 Spur Size 114  
 Pinion Size 30

## Transmission

Option 1  Option 2



## WHEELS, TYRES AND INSERTS

Wheels Schumacher  
 Tyres Sorex 32  
 Inserts JB  
 Tyre Additive Nosram Carpet  
 Additive Time 20 MIN (R) 20 MIN (F)  
 Tyre Warmers Yes  No

## DRIVER NOTES

OTM Steering, Middle Hole rear Hub  
 Gear Diff running Schue 100wt Oil  
 ESC Mounted Behind Lipo Cell

## Front Shocks

Oil Schue 45 WT  
 Springs Hara Grey  
 Piston Holes 2  3   
 length 12.7  
 Rebound 100 %

## FRONT SETTINGS

Drive Diff  Spool  One-Way  Height High  Low

Servo Saver Yes  No  Yoke Flex X  M  STD

Pivot Blocks Moulded (std)  Alloy

Screw Block Spacers Front 2.5 mm Rear 2.5 mm

Wishbone Quik-Klips Front 2.5 mm Rear 1.5 mm

Toe In-Out In-board  Out-board  0.5 °

Ride Height (Chassis to Floor) 5.2 mm

Droop On 10mm Block  Axle Height  5 mm

Anti-roll Bar No  1.20  1.40  1.60


Castor 0°  2°  4°  6°

Camber Positive  Negative  1.5 Deg




Link Washers Under Ball  Under Bracket  1 mm

Inboard Pin Kick-up  Anti-dive  Horizontal

Pivot Block Spacers Front 1.8 mm Rear 1.5 mm



Wishbone Flex CF  M



## Centre Track Rod

Washers 3 mm

## Link Mount

1 Groove - 45mm   
 2 Groove - 42mm   
 3 Groove - 39mm   
 4 Groove - 37mm

## REAR SETTINGS

Drive Height High  Low

Pivot Blocks Moulded (std)  Alloy

Screw Block Spacers Front 1.5 mm Rear 0.5 mm

Wishbone Quik-Klips Front 2.0mm Rear 2.0mm

Toe In In-board  3° Out-board  °

Ride Height (Chassis to Floor) 5.5 mm

Droop On 10mm Block  Axle Height  4.5 mm


Anti-roll Bar No  1.20  1.40  1.60

Camber Positive  Negative  2 Deg


Link Washers Under Ball  Under Bracket  0 mm

Inboard Pin Pro-Squat  Anti-Squat  Horizontal

Pivot Block Spacers Front 2.5 mm Rear 2.5 mm




Wishbone Flex CF  M



## Link Mount

1 Groove - 45mm   
 2 Groove - 42mm   
 3 Groove - 39mm   
 4 Groove - 37mm



## Rear Shocks

Oil Schue 45 WT  
 Springs Hara Grey  
 Piston Holes 2  3   
 length 12.7  
 Rebound 100 %