

DRIVER AND EVENT DETAILS

Name
 Date
 Event
 Weather
 Result

TRACK CONDITIONS

Grip Level High Medium Low
 Type Tight Open Both
 Surface Carpet Tarmac Wood
 Condition Smooth Bumpy
 Temperature °C °F
 Venue Indoor Outdoor



CHASSIS AND ELECTRICS

Chassis
 Top Deck
 Bodyshell
 Wing
 E.S.C.
 Servo
 Receiver
 Cells

MOTOR AND GEARING

Motor
 Rotor Diameter
 Timing
 Gear Pitch 48Dp 64Dp
 Spur Size
 Pinion Size

WHEELS, TYRES AND INSERTS

Wheels
 Tyres
 Inserts
 Tyre Additive
 Additive Time
 Tyre Warmers Yes No

DRIVER NOTES

warmers at 45 deg, Geared Diff with 900 cst oil, narrow front hexes, 0.5 against rear hex

Transmission

Option 1 Option 2


Front Shocks

Oil
 Springs
 Piston Holes 2 3
 length
 Rebound




FRONT SETTINGS

Drive Diff Spool One-Way Height High Low

Servo Saver Yes No Yoke Flex X M STD
 Pivot Blocks Moulded (std) Alloy
 Screw Block Spacers Front 2 mm Rear 2 mm
 Wishbone Quik-Klips Front 3 mm Rear 1 mm
 Toe In-Out In-board Out-board 0.5 °
 Ride Height (Chassis to Floor)
 Droop On 10mm Block Axle Height 5 mm
 Anti-roll Bar No 1.20 1.40 1.60
 Castor 0° 2° 4° 6°
 Camber Positive Negative 2 Deg
 Link Washers Under Ball Under Bracket 2 mm
 Inboard Pin Kick-up Anti-dive Horizontal
 Pivot Block Spacers Front 1.3 mm Rear 1 mm



Wishbone Flex CF M



Centre Track Rod

Washers 3 mm


Link Mount

1 Groove - 45mm
 2 Groove - 42mm
 3 Groove - 39mm
 4 Groove - 37mm


REAR SETTINGS

Drive Height High Low

Pivot Blocks Moulded (std) Alloy
 Screw Block Spacers Front 1.5 mm Rear 0.5 mm
 Wishbone Quik-Klips Front 2 mm Rear 2 mm
 Toe In In-board 3° Out-board °
 Ride Height (Chassis to Floor)
 Droop On 10mm Block Axle Height 4.5 mm
 Anti-roll Bar No 1.20 1.40 1.60
 Camber Positive Negative 2 Deg
 Link Washers Under Ball Under Bracket 0 mm
 Inboard Pin Pro-Squat Anti-Squat Horizontal




Wishbone Flex CF M



Link Mount

1 Groove - 45mm
 2 Groove - 42mm
 3 Groove - 39mm
 4 Groove - 37mm



Rear Shocks

Oil
 Springs
 Piston Holes 2 3
 length
 Rebound

Pivot block spacers, Front, 2mm Rear, 2mm