

## DRIVER AND EVENT DETAILS

Name   
 Date   
 Event   
 Weather   
 Result

## CHASSIS AND ELECTRICS

Chassis   
 Top Deck   
 Bodyshell   
 Wing   
 E.S.C   
 Servo   
 Receiver   
 Cells

## TRACK CONDITIONS

Grip Level  High  Medium  Low  
 Type  Tight  Open  Both  
 Surface  Carpet  Tarmac  Wood  
 Condition  Smooth  Bumpy  
 Temperature  °C   
 Venue  Indoor  Outdoor



## MOTOR AND GEARING

Motor   
 Rotor Diameter   
 Timing   
 Gear Pitch  48Dp  64Dp  
 Spur Size   
 Pinion Size

Transmission  
 Option 1  Option 2

## WHEELS, TYRES AND INSERTS

Wheels   
 Tyres   
 Inserts   
 Tyre Additive   
 Additive Time    
 Tyre Warmers  Yes  No

## DRIVER NOTES

Narrow front hex


## Front Shocks

Oil   
 Springs   
 Piston Holes  2  3  
 length   
 Rebound




## FRONT SETTINGS

Drive  Diff  Spool  One-Way  Height  High  Low

Servo Saver  Yes  No  Yoke Flex  X  M  STD  
 Pivot Blocks  Moulded (std)  Alloy  
 Screw Block Spacers    
 Wishbone Quik-Klips    
 Toe In-Out  In-board  Out-board   
 Ride Height (Chassis to Floor)   
 Droop  On 10mm Block  Axle Height   
 Anti-roll Bar  No  1.20  1.40  1.60  
 Castor  0°  2°  4°  6°  
 Camber  Positive  Negative   
 Link Washers  Under Ball  Under Bracket   
 Inboard Pin  Kick-up  Anti-dive  Horizontal   
 Pivot Block Spacers



Wishbone Flex  CF  M



## Centre Track Rod

Washers


## Link Mount

1 Groove - 45mm   
 2 Groove - 42mm   
 3 Groove - 39mm   
 4 Groove - 37mm


## REAR SETTINGS

Drive Height  High  Low

Pivot Blocks  Moulded (std)  Alloy  
 Screw Block Spacers    
 Wishbone Quik-Klips    
 Toe In  In-board  Out-board   
 Ride Height (Chassis to Floor)   
 Droop  On 10mm Block  Axle Height   
 Anti-roll Bar  No  1.20  1.40  1.60  
 Camber  Positive  Negative   
 Link Washers  Under Ball  Under Bracket   
 Inboard Pin  Pro-Squat  Anti-Squat  Horizontal   
 Pivot Block Spacers




Wishbone Flex  CF  M



## Link Mount

1 Groove - 45mm   
 2 Groove - 42mm   
 3 Groove - 39mm   
 4 Groove - 37mm

1.4mm   
 2.4mm   
 3.4mm   
 4.4mm



## Rear Shocks

Oil   
 Springs   
 Piston Holes  2  3  
 length   
 Rebound