

## DRIVER AND EVENT DETAILS

Name **Scott Guyatt**  
 Date **7 March 2010**  
 Event **Tasmanian Championships**  
 Weather **Fine, 25 degrees**  
 Result **TQ & 1st**

## CHASSIS AND ELECTRICS

Chassis **Mi4-LP 2.0mm**  
 Top Deck **2.0mm**  
 Bodyshell **Protoform Mazda Speed 6**  
 Wing **Std**  
 E.S.C **LRP SPX Stockspec**  
 Servo **Futaba S9402**  
 Receiver **Spectrum**  
 Cells **IP5000/40C**

## TRACK CONDITIONS

Grip Level **High**  **Medium**  **Low**   
 Type **Tight**  **Open**  **Both**   
 Surface **Carpet**  **Tarmac**  **Wood**   
 Condition **Smooth**  **Bumpy**   
 Temperature **25** °C °F  
 Venue **Indoor**  **Outdoor**

## MOTOR AND GEARING

Motor **Speedpassion 3.0 10.5 turn**  
 Rotor Diameter **std**  
 Timing **max**  
 Gear Pitch **48Dp**  **64Dp**   
 Spur Size **85**  
 Pinion Size **28**

### Transmission

Option 1  Option 2



## WHEELS, TYRES AND INSERTS

Wheels **Schumacher Revlite**  
 Tyres **Sorex 36**  
 Inserts **Sorex C Medium**  
 Tyre Additive **Rheinard**  
 Additive Time **20 MIN (R) 20 MIN (F)**  
 Tyre Warmers **Yes**  **No**

## DRIVER NOTES


### Front Shocks

Oil **35 WT**  
 Springs **HPI Silver**  
 Piston Holes **2**  **3**   
 length  
 Rebound **90 %**




## FRONT SETTINGS

Drive **Diff**  **Spool**  **One-Way**  **Height** **High**  **Low**

Servo Saver **Yes**  **No**  **Yoke Flex** **X**  **M**  **STD**   
 Pivot Blocks **Moulded (std)**  **Alloy**   
 Screw Block Spacers **Front 1** mm **Rear 1** mm  
 Wishbone Quik-Klips **Front 2** mm **Rear 2** mm  
 Toe In-Out **In-board**  **Out-board**  **+1** °  
 Ride Height (Chassis to Floor) **5.2** mm  
 Droop **On 10mm Block**  **Axle Height**  **4.5** mm  
 Anti-roll Bar **No**  **1.20**  **1.40**  **1.60**   
 Castor **0°**  **2°**  **4°**  **6°**   
 Camber **Positive**  **Negative**  **2 Deg**  
 Link Washers **Under Ball**  **Under Bracket**  **0** mm  
 Inboard Pin **Kick-up**  **Anti-dive**  **Horizontal**   
 Pivot Block Spacers **Front** mm **Rear** mm



Wishbone Flex **CF**  **M**




### Centre Track Rod

Washers **3** mm

### Link Mount


**1 Groove**   
**2 Groove**   
**3 Groove**




## REAR SETTINGS

Drive **Height** **High**  **Low**

Pivot Blocks **Moulded (std)**  **Alloy**   
 Screw Block Spacers **Front 1.5** mm **Rear 1.5** mm  
 Wishbone Quik-Klips **Front 1** mm **Rear 3** mm  
 Toe In **In-board**  **2.5°** **Out-board**  °  
 Ride Height (Chassis to Floor) **5.8** mm  
 Droop **On 10mm Block**  **Axle Height**  **4.5** mm  
 Anti-roll Bar **No**  **1.20**  **1.40**  **1.60**   
 Camber **Positive**  **Negative**  **2 Deg**  
 Link Washers **Under Ball**  **Under Bracket**  **0** mm  
 Inboard Pin **Pro-Squat**  **Anti-Squat**  **Horizontal**   
 Pivot Block Spacers **Front** mm **Rear** mm







Wishbone Flex **CF**  **M**



### Link Mount

**1 Groove**   
**2 Groove**   
**3 Groove**



### Rear Shocks

Oil **35 WT**  
 Springs **HPI Silver**  
 Piston Holes **2**  **3**   
 length  
 Rebound **90 %**