



Carbon/Carbon Composite

SST Mission Set Up Sheet

Driver; Simon Welch

Circuit; WLRC

Meeting; KO Grand Prix

Date; 24-25/08/02

Notes & Circuit Conditions:

Qual 8th. Fin 8th

Front Suspension:

Anti Roll Bar; Y/N thin/thick

Shock Position; 1-2-3-4-5

Toe In; 0 deg.

Castor; 6 deg.

Camber; 1 deg.

Ride Height; 5 mm.

Shock Oil; 50

Shock Piston; 3

Spring; Red

Centre Track Rod Length; Std

On Wishbone; 1-2

Inboard toe out; Y/N

Lower Wishbone; Forward/Rear

Upper Susp. Mount Position; 1-2

Shock Length; 66.5 mm.

Droop; mm.

Hub Carrier position; 1-2

Steering arm position; 1-2

Rear Suspension:

Anti Roll Bar; Y/N thin/thick

Shock Position; 1-2-3-4-5

Toe In; 1 deg.

Camber; 2 deg.

Anti Squat;

Ride Height; 5 mm.

Shock Oil; 55

Shock Piston; 3

Spring; Red

On Wishbone; 1-2

Inboard toe in; 0-2 deg.

Lower Wishbone; Forw/Mid/Rear

Upper Susp. Mount Position; 1-2

Hub Carrier position; 1-2 (1=in-line)

Shock Length; 66.5 mm.

Droop; mm.

Front Tyre; CS-22

Rear Tyre; CS-22

Front Insert; Yokomo (m)

Rear Insert; Yokomo (m)

Pinion; 26 teeth

Spur Gear; 84 teeth

Pulley Size; 17t/20t

Front One Way; Y/N

Front D/Shaft; Plastic

Rear D/Shaft; Plastic

Motor; Orion Core 12x1

Speedo; MRT VFX FP

Cells; Sanyo 3000HV

Receiver; KO

Servo; KO713

Body; Vectra