

DRIVER, TRACK AND RESULTS

DRIVER **Viktor Wilck** COUNTRY **Sweden** WEATHER AIR TEMP **25c** TRACK TEMP **25c** DRY INTERMEDIATE WET

TRACK **ETS rd1 2017-18** SURFACE ASPHALT CARPET TRACTION LOW MEDIUM HIGH COMMENTS **-**

RACE **ETS rd1 2017-18** DATE **2017-10-29** QUALY POS. **-** QUALY TIME **-** STARTING POS. **-** FINAL POS. **-**

FRONT	DRIVE TRAIN	REAR
<input type="checkbox"/> GEAR DIFF	cst	<input checked="" type="checkbox"/> GEAR DIFF 8.000 cst
<input checked="" type="checkbox"/> SPOOL		

FLEX CONFIGURATION		
CHASSIS	STIFFENERS	TOP DECK
<input checked="" type="checkbox"/> STD <input type="checkbox"/> FLEX	<input type="checkbox"/> FRONT <input type="checkbox"/> REAR	<input type="checkbox"/> NONE <input checked="" type="checkbox"/> 3mm

FRONT	HEAVE DAMPER	REAR
OIL 1000 cst	OIL 1500 cst	
SPRINGS orange	SPRINGS red	
<input type="checkbox"/> <input type="checkbox"/> <input checked="" type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input checked="" type="checkbox"/>	
N HOLES 2 ∅ mm	N HOLES 2 ∅ mm	

FRONT	ROLL DAMPER	REAR
OIL 3000 cst	OIL 3000 cst	
SPRINGS pink	SPRINGS blue	
<input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	
N HOLES 0 ∅ mm	N HOLES 0 ∅ mm	

FRONT	TYRES	REAR
	Controlled Tyre <input checked="" type="checkbox"/>	
ETS Volante	MAKE AND TYPE	ETS Volante
ETS Volante	INSERTS	ETS Volante
ETS	ADDITIVE	ETS
15min	ADDITIVE TIMING	15min

ELECTRONICS	
BATTERY	
BRAND Arrowmax	CAPACITY 5200 mAh
MOTOR	
BRAND DASH by AM	TYPE 4.5t TIMING 30
ESC	
BRAND DASH by AM	TYPE

RATIO CONFIGURATION	
64	PITCH SPUR GEAR TEETH 112
64	PITCH PINION TEETH 30
FINAL DRIVE RATIO 7.46	ROLL OUT -mm

AERODYNAMIC CONFIGURATION	
BODY BRAND PF	
BODY TYPE LTC-r	
BODY POSITION 10mm	

REMARKS

FRONT	REAR
PULLROD LENGTH short opt mm	PULLROD LENGTH short opt mm
ROLL CENTER SHIMS 3 mm	ROLL CENTER SHIMS 2.5 mm
WHEEL HEX -0.75 mm	WHEEL HEX -0.75 mm
DOWN STOP 2 mm	DOWN STOP 1 mm

FRONT	REAR
UPPER ARM INSERT	UPPER ARM INSERT
FRONT CAMBER R 2° L 2°	REAR CAMBER R 2° L 2°
RIDE HEIGHT 5.0 mm WITH TYRE ∅ volante mm	RIDE HEIGHT 5.3 mm WITH TYRE ∅ volante mm

FRONT	REAR
CASTER 3 mm	SPACERS 6 mm
FRONT TOE 1°	REAR TOE 2.25°
OUTER ACKERMANN	INNER ACKERMANN
	REAR REACTIVE SYSTEM
	SHIMS 0 mm

FRONT	REAR
WHEEL BASE <input type="checkbox"/> 0 <input type="checkbox"/> 1 <input checked="" type="checkbox"/> 2 <input type="checkbox"/> 3 <input type="checkbox"/> 4	WHEEL BASE <input type="checkbox"/> 0 <input type="checkbox"/> 1 <input type="checkbox"/> 2 <input checked="" type="checkbox"/> 3 <input type="checkbox"/> 4
SHIMS mm	SHIMS mm

FRONT	REAR
ROLL CENTER BOTTOM INSERTS MID LOW <input checked="" type="checkbox"/> MID HIGH <input type="checkbox"/> HIGH <input type="checkbox"/>	ROLL CENTER BOTTOM INSERTS MID LOW <input checked="" type="checkbox"/> MID HIGH <input type="checkbox"/> HIGH <input type="checkbox"/>

WEIGHT DISTRIBUTION	
TRACK WIDTH 186 mm	CAR WEIGHT 1355 grams
	BATTERY POS. <input checked="" type="checkbox"/> FR <input type="checkbox"/> MID <input type="checkbox"/> RR
	TRACK WIDTH 185 mm