

# SETUP SHEET



TRACK CONDITIONS							
Size:	low	<u>1</u>	2	3	4	5	high
Traction:	low	1	2	<u>3</u>	<u>4</u>	5	high

Track Temp/Air Temp: \_\_\_\_\_° / 26°  
 Best Lap: \_\_\_\_\_  
 Note: \_\_\_\_\_

### FRONT

Stabilizer Length \_\_\_\_\_ mm

Down Stop \_\_\_\_\_ mm

F \_\_\_\_\_ mm R \_\_\_\_\_ mm

Camber Angle 2 °  
 Castor 3 °  
 Ride Height 5.5 mm  
 Down Stop 3.5 mm  
 Front Drive Diff One-Way Spood  
 Stabilizer 1.1 1.2 1.3 1.4 1.5 mm  
 Stabilizer Length \_\_\_\_\_ mm  
 Notes \_\_\_\_\_

### SHOCKS

	Front	Rear
Piston	Hole Size <u>Kit</u> mm	Hole Size <u>Kit</u> mm
	#of Holes 1 2 3	#of Holes 1 2 3
Oil wt.	<u>30</u>	<u>30</u>
Oil Brand	<u>Much More</u>	<u>Much More</u>
Springs	<u>Purple</u>	<u>Purple</u>
Oring	<u>Kit</u>	<u>Kit</u>
Bladder note		
Front	_____ mm	_____ mm
Rear	_____ mm	_____ mm

Thread Length \_\_\_\_\_ mm

### REAR

Stabilizer Length \_\_\_\_\_ mm

Shim \_\_\_\_\_ mm

Down Stop \_\_\_\_\_ mm

F \_\_\_\_\_ mm R \_\_\_\_\_ mm

Camber Angle 2 °  
 Ride Height 5.5 mm  
 Down Stop 4.0 mm  
 Stabilizer 1.1 1.2 1.3 1.4 1.5 mm  
 Stabilizer Length \_\_\_\_\_ mm  
 Shim 0 mm  
 Rear Wheelbase Kit °  
 Notes \_\_\_\_\_

### TIRES

	Front	Rear
Brand	<u>Sorex</u>	<u>Sorex</u>
Compound	<u>36R</u>	<u>36R</u>
Insert	<u>C med</u>	<u>C med</u>
Wheel	<u>Proline</u>	<u>Proline</u>
Traction Compound	<u>Much More Red Sap</u>	<u>Much More Red Sap</u>
Notes	<u>5 Cells Battery Position</u>	

F Toe Angle 0 ° R Toe Angle Kit °

1 3 mm 2

Body DNA2  
 Wing Kit

Spur & Pinion  
 Spur (S) 110  
 Pinion (P) 23 →  $\frac{S}{P} = \frac{110}{23} \approx 4.78$  X2.0588=R  
 Final Drive Ratio (R) \_\_\_\_\_

Wheel Hubs  
 F Widthspacer 0 mm  
 R Widthspacer 0 mm

Front Width Kit mm  
 Rear Width Kit mm

R Upright spacer  
 Front \_\_\_\_\_ mm Rear \_\_\_\_\_ mm

Electronics  
 Transmitter KO  
 Receiver Spectrum  
 Servo KO  
 ESC Novak  
 Battery Int 4200

Motor  
 Brand Orion  
 Turns 3.5  
 Brushes none  
 Springs none  
 Timing none