

# SETUP SHEET



TRACK CONDITIONS							
Size:	low	1	<b>2</b>	3	4	5 high	Track Temp/Air Temp: _____° / <u>30</u> °
Traction:	low	1	2	3	<b>4</b>	5 high	Best Lap: <u>11' 6"</u>
							Note: _____

### FRONT

Stabilizer Length \_\_\_\_\_

Camber Angle -1.5 °

Castor 3 °

Ride Height 5.5 mm

Down Stop 3 mm

Front Drive Diff One-Way **Spood**

Stabilizer 1.1 **1.2** 1.3 1.4 1.5 mm

Stabilizer Length 0 mm

Notes \_\_\_\_\_

F 1 mm R 1 mm

### SHOCKS

	Front	Rear
Piston	Hole Size <u>Std</u> mm	Hole Size <u>Std</u> mm
#of Holes	1 <b>2</b> 3	1 <b>2</b> 3
Oil wt.	<u>35</u>	<u>35</u>
Oil Brand	<u>Much More</u>	<u>Much More</u>
Springs	<u>Std</u>	<u>Std</u>
O-ring	<u>Std</u>	<u>Std</u>
Bladder note		
Front	_____ mm	_____ mm
Rear	_____ mm	_____ mm

Thread Length \_\_\_\_\_

### REAR

Stabilizer Length \_\_\_\_\_

Camber Angle -1.5 °

Ride Height 6.5 mm

Down Stop 0 mm

Stabilizer 1.1 **1.2** 1.3 1.4 1.5 mm

Stabilizer Length 0 mm

Shim 0 mm

Rear Wheelbase Short °

Notes \_\_\_\_\_

F 1 mm R 1 mm

### TIRES

	Front	Rear
Brand	<u>Sorex</u>	<u>Sorex</u>
Compound	<u>36R</u>	<u>36R</u>
Insert	<u>C med</u>	<u>C med</u>
Wheel	<u>Proline</u>	<u>Proline</u>
Traction Compound	<u>Z1</u>	<u>Z1</u>
Notes	<u>Stiff center brace, 5 Cells</u>	
	<u>Batteries in forward Position</u>	

F Toe Angle 0 ° R Toe Angle 2.5 °

F Widthspacer 0 mm R Widthspacer 0.5 mm

Front Width 188 mm

Rear Width 189 mm

R Upright spacer Front \_\_\_\_\_ mm Rear \_\_\_\_\_ mm

Body SMAROS 30

Wing std

Spur & Pinion  
 Spur (S) 110  
 Pinion (P) 25 }  $\frac{S}{P} = \frac{110}{25} = 4.4$  X2.0588=R

Final Drive Ratio (R) 9.0S8

Wheel Hubs

Electronics  
 Transmitter KO  
 Receiver KO  
 Servo KO  
 ESC Novak  
 Battery Fantom K200

Motor  
 Brand Team Orion  
 Turns 3.5  
 Brushes \_\_\_\_\_  
 Springs \_\_\_\_\_  
 Timing \_\_\_\_\_