

SETUP SHEET



TRACK CONDITIONS						Track Temp/Air Temp: _____° / _____°		
Size:	low	<u>1</u>	2	3	4	5	high	Best Lap: <u>10'21</u>
Traction:	low	1	2	3	<u>4</u>	5	high	

FRONT

Stabilizer Length _____ mm

Camber Angle 0 °

Castor 3 °

Ride Height 5.5 mm

Down Stop 4 mm

Front Drive Diff One-Way Spood

Stabilizer 1.1 1.2 1.3 1.4 1.5 mm

Stabilizer Length _____ mm

Notes _____

SHOCKS

	Front	Rear
Piston	Hole Size _____ mm	Hole Size _____ mm
#of Holes	1 <u>2</u> 3	1 <u>2</u> 3
Oil wt.	<u>300</u>	<u>300</u>
Oil Brand	<u>TEAM MAGIC</u>	<u>TEAM MAGIC</u>
Springs	<u>STD</u>	<u>STD</u>
Oring	<u>STD</u>	<u>STD</u>
Bladder note		
Front	_____ mm	_____ mm
Rear	_____ mm	_____ mm

Thread Length _____ mm

REAR

Stabilizer Length _____ mm

Camber Angle 2 °

Ride Height 6 mm

Down Stop 4 mm

Stabilizer 1.1 1.2 1.3 1.4 1.5 mm

Stabilizer Length _____ mm

Shim 0 mm

Rear Wheelbase _____ °

Notes _____

TIRES

	Front	Rear
Brand	<u>SOREX 36R</u>	<u>SOREX 36R</u>
Compound		
Insert	<u>GM</u>	<u>GM</u>
Wheel	<u>GM</u>	<u>GM</u>
Traction Compound	<u>CORALLY</u>	<u>CORALLY</u>
Notes	<u>TRAITEMENT PENDANT 30 MINUTES</u>	

F Toe Angle 0 ° R Toe Angle 2.5 °

F Widthspacer 0 mm R Widthspacer 0 mm

Front Width 185 mm

Rear Width 185 mm

R Upright spacer Front 0.9 mm Rear 0.9 mm

Body STRATUS 3

Wing EFRA

Spur (S) 84

Pinion (P) 28

Final Drive Ratio (R) 6.17

Electronics

Transmitter SANWA MII

Receiver SANWA

Servo ERG RZ SANWA

ESC TEKIN RI

Battery ORION 4200 SHO

Motor

Brand CORALLY

Turns 17T

Brushes CS

Springs HARD

Timing _____