

TRACK CONDITIONS

Type :	<input checked="" type="checkbox"/> Carpet	<input type="checkbox"/> Asphalt	Size:	<input type="checkbox"/> Open	<input type="checkbox"/> Med.	<input checked="" type="checkbox"/> Tight
Place :	<input checked="" type="checkbox"/> Indoor	<input type="checkbox"/> Outdoor	Traction:	<input type="checkbox"/> High	<input checked="" type="checkbox"/> Med.	<input type="checkbox"/> Low
Surface:	<input type="checkbox"/> Smooth	<input checked="" type="checkbox"/> Med.	<input type="checkbox"/> Bumpy	Track Temp/Air Temp: <u>23</u> / <u>23</u>		

Note: _____

FRONT SUSPENSION

Track Width: 186 mm Gear Diff _____ wt
 Toe Angle: 0.5 ° Solid Axle (Spool)
 Caster: 4 ° One Way
 Camber: -1.5 °
 Ride Height: 5 mm Anti-Roll Bar: \varnothing 1.4 mm
 Down Stop: 6 mm

Hex Adapter: origin

Diff. High Low

Shims: +0.75, 0, -0.75

REAR SUSPENSION

Track Width: 189 mm Gear Diff 1000 wt
 Toe Angle: 3 °
 Camber: -2 °
 Ride Height: 5.5 mm
 Down Stop: 6 mm Anti-Roll Bar: \varnothing 1.2 mm

Motor Position: Inside (0mm) Outside (1mm) _____ mm

Hex Adapter: Origin

Diff. High Low

Shims: +0.75, 0, -0.75

STIFF SETTING

Upper Deck: 2.0mm 2.3mm 2.5mm

Chassis: 2.3mm 2.5mm 3.0mm

ELECTRONICS

Servo: KO 2413 ICS
 ESC: HW V3.1
 Battery: CS 7200

DRIVE RATIO

Spur 110 T
 Pinion 40 T $\times 1.9 =$ 5.23

MOTOR

Brand: Speed passion
 Turns: 10.5
 Timing: 20°

TIRES

Insert: _____
 Wheel: LRP CPX
 Shore/deg: _____
 Compound: _____
 Tire Temp: _____
 Tire additive: Greenn RC 6001
 Treated Area

ESC

Punch: _____
 Initial Brake: _____
 Drag Brake: 2
 ESC Timing Turbo Timing

FL FR RL RR

SHOCKS

Hole Size: F 1.1 R 1.1
 Holes In Piston: F 3 R 3
 Oil wt: F 600 TM R 600 TM
 Springs: F KF 27 R KF 25
 Rebound: F 25% R 25%
 Bladder Note: _____
 Thread Length: F R

BODY

Body: LTCR
 Wing Height: EFRA
 Wing Position: Maxi EFRA