

| TRACK CONDITIONS |                                 |  |  |
|------------------|---------------------------------|--|--|
| Type :           | <input type="checkbox"/> Carpet | <input type="checkbox"/> Asphalt                             | Size: <input type="checkbox"/> Open <input type="checkbox"/> Med. <input type="checkbox"/> Tight   |
| Place :          | <input type="checkbox"/> Indoor | <input type="checkbox"/> Outdoor                             | Traction: <input type="checkbox"/> High <input type="checkbox"/> Med. <input type="checkbox"/> Low |
| Surface:         | <input type="checkbox"/> Smooth | <input type="checkbox"/> Med. <input type="checkbox"/> Bumpy | Track Temp/Air Temp: _____ / _____   |
| Note: _____      |                                 |  |  |

| FRONT SUSPENSION      |   |
|-----------------------|---|
| Track Width: _____ mm | <input type="checkbox"/> Gear Diff _____ wt |
| Toe Angle: _____ °    | <input type="checkbox"/> Ball Diff          |
| Caster: _____ °       | <input type="checkbox"/> One Way            |
| Camber: _____ °       | <input type="checkbox"/> Solid Axle         |
| Ride Height: _____ mm | Anti-Roll Bar: ∅ _____ mm                   |
| Down Stop: _____ mm   |   |

| REAR SUSPENSION       |   |
|-----------------------|---|
| Track Width: _____ mm | <input type="checkbox"/> Gear Diff _____ wt |
| Toe Angle: _____ °    | <input type="checkbox"/> Ball Diff          |
| Camber: _____ °       | <input type="checkbox"/> Solid Axle         |
| Ride Height: _____ mm |   |
| Down Stop: _____ mm   | Anti-Roll Bar: ∅ _____ mm                   |

| STIFF SETTING                        |                                   |
|--------------------------------------|-----------------------------------|
| <p>Upper Deck: 2.0mm 2.3mm 2.5mm</p> | <p>Chassis: 2.3mm 2.5mm 3.0mm</p> |

| ELECTRONICS    |
|----------------|
| Servo: _____   |
| ESC: _____     |
| Battery: _____ |

| DRIVE RATIO                           |
|---------------------------------------|
| Spur $\frac{T}{T} \times 1.9 =$ _____ |
| Pinion _____                          |

| MOTOR         |
|---------------|
| Brand: _____  |
| Turns: _____  |
| Timing: _____ |

| TIRES                |
|----------------------|
| Insert: _____        |
| Wheel: _____         |
| Shore/deg: _____     |
| Compound: _____      |
| Tire Temp: _____     |
| Tire additive: _____ |
| Treated Area         |

| SHOCKS |                                  |
|--------|----------------------------------|
|        | Hole Size: F _____ R _____       |
|        | Holes In Piston: F _____ R _____ |
|        | Oil wt: F _____ R _____          |
|        | Springs: F _____ R _____         |
|        | Rebound: F _____ R _____         |
|        | Bladder Note: _____              |
|        | Thread Length: F _____ R _____   |

| ESC   |
|---|
| Punch: _____  |
| Initial Brake: _____  |
| Drag Brake: _____   |
| <input type="checkbox"/> ESC Timing <input type="checkbox"/> Turbo Timing |

|    |    |    |    |
|----|----|----|----|
|    |    |    |    |
| FL | FR | RL | RR |

| BODY |                      |
|------|----------------------|
|      | Body: _____          |
|      | Wing Height: _____   |
|      | Wing Position: _____ |