

TRACK CONDITIONS						
Type:	<input type="checkbox"/> Carpet	<input checked="" type="checkbox"/> Asphalt	Size:	<input type="checkbox"/> Open	<input checked="" type="checkbox"/> Med.	<input type="checkbox"/> Tight
Place:	<input type="checkbox"/> Indoor	<input checked="" type="checkbox"/> Outdoor	Traction:	<input type="checkbox"/> High	<input checked="" type="checkbox"/> Med.	<input type="checkbox"/> Low
Surface:	<input type="checkbox"/> Smooth	<input checked="" type="checkbox"/> Med.	<input type="checkbox"/> Bumpy	Track Temp/Air Temp: _____ / <u>20</u>		
Note: _____						

FRONT SUSPENSION	
Track Width: <u>kit</u> mm	<input type="checkbox"/> Gear Diff _____ wt
Toe Angle: <u>0.5</u> °	<input type="checkbox"/> One Way
Caster: <u>4</u> °	<input checked="" type="checkbox"/> Spool
Camber: <u>1.5</u> °	
Ride Height: <u>5.2</u> mm	Anti-Roll Bar: \varnothing <u>1.3</u> mm
Down Stop: <u>4.5</u> mm	

FF Arm Insert

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

FF Arm Mount

- #3 (+2 mm)
- #2 (kit 0 mm)
- #1 (-2 mm)

FR Arm Mount

- #3 (+2 mm)
- #2 (kit 0 mm)
- #1 (-2 mm)

FR Arm Insert

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

RR Arm Mount

- #3 (+2 mm)
- #2 (kit 0 mm)
- #1 (-2 mm)

RR Arm Insert

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

REAR SUSPENSION	
Track Width: <u>kit</u> mm	<input checked="" type="checkbox"/> Gear Diff <u>4000</u> wt
Toe Angle: <u>3.0</u> °	
Camber: <u>1.5</u> °	
Ride Height: <u>5.4</u> mm	
Down Stop: <u>4.5</u> mm	Anti-Roll Bar: \varnothing <u>1.2</u> mm

RF Arm Insert

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

RF Arm Mount

- #3 (+2 mm)
- #2 (kit 0 mm)
- #1 (-2 mm)

RR Arm Mount

- #3 (+2 mm)
- #2 (kit 0 mm)
- #1 (-2 mm)

RR Arm Insert

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

Motor Position:

- Inside (0mm)
- Outside (1mm)

Chassis: 2.3 mm 2.5 mm Aluminum


Upper Deck: 2 mm 2.3 mm 2.5 mm

ELECTRONICS
Servo: <u>HRC Low Profil</u>
ESC: <u>Muchmore</u>
Battery: <u>Muchmore</u>

DRIVE RATIO
Spur <u>79</u> T
Pinion <u>30</u> T $\times 1.9 =$ <u>5.00</u>

MOTOR
Brand: <u>Muchmore</u>
Turns: <u>13.5</u>
Timing: <u>0</u>

TIRES
Insert: <u>Volante</u>
Wheel: _____
Shore/deg: <u>36</u>
Compound: _____
Tire Temp: <u>70</u>
Tire additive: <u>Handout</u>
Treated Area



ESC
Punch: <u>12</u>
Initial Brake: <u>0</u>
Drag Brake: <u>0</u>
<input type="checkbox"/> ESC Timing <input type="checkbox"/> Turbo Timing

SHOCKS	
	Hole Size: <u>F kit</u> <u>R kit</u>
	Holes In Piston: <u>F kit</u> <u>R kit</u>
	Shock Oil WT: <u>F 40</u> <u>R 40</u>
	Shock Springs: <u>F TM P2.9</u> <u>R TM P2.5</u>
	Shock Rebound: <u>F 25%</u> <u>R 25%</u>
	Bladder Note: _____
	Thread Length: <u>F</u> <u>R</u>
	Shock Length: <u>F</u> <u>R</u>

BODY	
	Body Position: <u>+3mm</u>
	Body: <u>Mazda6</u>
	Wing Height: <u>max</u>
	Wing Position: <u>max</u>