



SETUP SHEET



TRACK CONDITIONS			
Type :	<input checked="" type="checkbox"/> Carpet	<input type="checkbox"/> Asphalt	Size: <input type="checkbox"/> Open <input checked="" type="checkbox"/> Med. <input type="checkbox"/> Tight
Place :	<input checked="" type="checkbox"/> Indoor	<input type="checkbox"/> Outdoor	Traction: <input type="checkbox"/> High <input checked="" type="checkbox"/> Med. <input type="checkbox"/> Low
Surface:	<input type="checkbox"/> Smooth <input checked="" type="checkbox"/> Med. <input type="checkbox"/> Bumpy	Track Temp/Air Temp: _____ / _____	
Note: _____			

FRONT SUSPENSION	
Track Width: _____ mm	<input type="checkbox"/> Gear Diff _____ wt
Toe Angle: <u>0</u> °	<input type="checkbox"/> One Way
Caster: <u>4</u> °	<input checked="" type="checkbox"/> Spool
Camber: <u>1.5</u> °	
Ride Height: <u>5</u> mm	Anti-Roll Bar: <u>Ø 1.3</u> mm
Down Stop: <u>5</u> mm	

Shim: 1 mm

Shim: 1.5 mm

Hex Adapter: Kit

Diff. High Low

Shim: 0 mm

Shim: 2 mm

Shim: 1 mm

Shim: 1 mm

Shim: 1 mm

Shim: 1 mm

Shim: 1 mm

FF Arm Insert

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

FF Arm Mount

- #3 (+2 mm)
- #2 (kit 0 mm)
- #1 (-2 mm)

FR Arm Mount

- #3 (+2 mm)
- #2 (kit 0 mm)
- #1 (-2 mm)

FR Arm Insert

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

REAR SUSPENSION	
Track Width: _____ mm	<input checked="" type="checkbox"/> Gear Diff <u>3'000</u> wt
Toe Angle: _____ °	
Camber: <u>1.5</u> °	
Ride Height: <u>5</u> mm	
Down Stop: <u>4</u> mm	Anti-Roll Bar: <u>Ø 1.2</u> mm

Shim: 4 mm

Shim: 1 mm

Hex Adapter: Kit

Diff. High Low

Shim: 2 mm

Shim: 1 mm

Shim: 1 mm

Shim: 1 mm

Shim: 1 mm

Shim: 1 mm

RF Arm Insert

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

RF Arm Mount

- #3 (+2 mm)
- #2 (kit 0 mm)
- #1 (-2 mm)

RR Arm Mount

- #3 (+2 mm)
- #2 (kit 0 mm)
- #1 (-2 mm)

RR Arm Insert

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

Motor Position :

- Inside (0mm)
- Outside (1mm)
- _____ mm

Chassis: 2.3 mm 2.5 mm Aluminum

Upper Deck: 2 mm 2.3 mm 2.5 mm


3D Flex Fixed Post

ELECTRONICS
Servo: _____
ESC: _____
Battery: _____

DRIVE RATIO
Spur $\frac{0}{1} T \times 1.9 =$ <u>0.00</u>
Pinion $\frac{1}{1} T$

MOTOR
Brand: _____
Turns: _____
Timing: _____

TIRES
Insert : _____
Wheel: <u>Team Powers</u>
Shore/deg: <u>26R</u>
Compound: _____
Tire Temp: _____
Tire additive: <u>Hudy 20mins</u>
Treated Area



ESC
Punch: _____
Initial Brake: _____
Drag Brake: _____
<input type="checkbox"/> ESC Timing <input type="checkbox"/> Turbo Timing

SHOCKS
Hole Size: <u>F 1.1</u> <u>R 1.1</u>
Holes In Piston: <u>F 3</u> <u>R 3</u>
Shock Oil WT: <u>F 450</u> <u>R 450</u>
Shock Springs: <u>F Yok Blue</u> <u>R Yok Blue</u>
Shock Rebound: <u>F</u> <u>R</u>
Bladder Note: _____
Thread Length: <u>F</u> <u>R</u>
Shock Length: <u>F</u> <u>R</u>

BODY	
Body Position: _____	Body: _____
	Wing Height: _____
	Wing Position: _____