

TRACK CONDITIONS						
Type:	<input type="checkbox"/> Carpet	<input checked="" type="checkbox"/> Asphalt	Size:	<input type="checkbox"/> Open	<input type="checkbox"/> Med.	<input checked="" type="checkbox"/> Tight
Place:	<input type="checkbox"/> Indoor	<input checked="" type="checkbox"/> Outdoor	Traction:	<input type="checkbox"/> High	<input checked="" type="checkbox"/> Med.	<input type="checkbox"/> Low
Surface:	<input type="checkbox"/> Smooth	<input type="checkbox"/> Med.	<input type="checkbox"/> Bumpy	Track Temp/Air Temp: 34 / 23		
Note: _____						

FRONT SUSPENSION

Track Width: _____ mm Gear Diff _____ wt

Toe Angle: _____ ° One Way

Caster: 4 ° Spool

Camber: 2 °

Ride Height: 5 mm Anti-Roll Bar: Ø 1,4 mm

Down Stop: 31,4 mm

FF Arm Insert

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

FF Arm Mount

- #3 (+2 mm)
- #2 (kit 0 mm)
- #1 (-2 mm)

Shim: 1 mm

Shim: 2 mm

Hex Adapter: kit

Diff.

- High
- Low

FR Arm Mount

- #3 (+2 mm)
- #2 (kit 0 mm)
- #1 (-2 mm)

FR Arm Insert

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

Shim: 1 mm

Shim: 3 mm

Shim: 1,5 mm

Shim: 0 mm

REAR SUSPENSION

Track Width: _____ mm Gear Diff 3000 wt

Toe Angle: _____ °

Camber: 1,5 °

Ride Height: 5,2 mm

Down Stop: 30,4 mm Anti-Roll Bar: Ø 1,2 mm

Shim: 3,5 mm

Shim: 2,25 mm

Hex Adapter: kit

Diff.

- High
- Low

RF Arm Insert

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

RF Arm Mount

- #3 (+2 mm)
- #2 (kit 0 mm)
- #1 (-2 mm)

RR Arm Mount

- #3 (+2 mm)
- #2 (kit 0 mm)
- #1 (-2 mm)

RR Arm Insert

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

Shim: 1 mm

Shim: 0,2 mm

Shim: 2 mm

Shim: 0,2 mm

Motor Position:

- Inside (0mm)
- Outside (1mm)

Chassis: 2.3 mm 2.5 mm Aluminum

Upper Deck: 2 mm 2.3 mm 2.5 mm

ELECTRONICS

Servo: Sanwa

ESC: SXX V2

Battery: EZ 6200

MOTOR

Brand: LRP x20

Turns: 13,5

Timing: timing set

ESC

Punch: 10

Initial Brake: 0

Drag Brake: 0

ESC Timing Turbo Timing

DRIVE RATIO

Spur 96 T

Pinion 45 T X1.9 = 4.05

TIRES

Insert: G32

Wheel: G32

Shore/deg: G32

Compound: _____

Tire Temp: 65

Tire additive: carpet2

Treated Area

FL FR RL RR

SHOCKS

Hole Size: F 1,1 R 1,1

Holes In Piston: F 3 R 3

Shock Oil WT: F 400 R 400

Shock Springs: F L2,9 R L2,8

Shock Rebound: F 4mm R 4mm

Bladder Note: _____

Thread Length: F _____ R _____

Shock Length: F _____ R _____

BODY

Body Position: +4

Body: HB MPS LW

Wing Height: -1

Wing Position: +8