

SETUP SHEET



TRACK CONDITIONS						
Type:	<input checked="" type="checkbox"/> Carpet	<input type="checkbox"/> Asphalt	Size:	<input type="checkbox"/> Open	<input checked="" type="checkbox"/> Med.	<input type="checkbox"/> Tight
Place:	<input checked="" type="checkbox"/> Indoor	<input type="checkbox"/> Outdoor	Traction:	<input checked="" type="checkbox"/> High	<input type="checkbox"/> Med.	<input type="checkbox"/> Low
Surface:	<input type="checkbox"/> Smooth	<input checked="" type="checkbox"/> Med.	<input type="checkbox"/> Bumpy	Track Temp/Air Temp: _____ / _____		
Note: _____						

FRONT SUSPENSION	
Track Width: _____ mm	<input type="checkbox"/> Gear Diff _____ wt
Toe Angle: _____ °	<input type="checkbox"/> One Way
Caster: <u>4</u> °	<input checked="" type="checkbox"/> Spool
Camber: <u>1.5</u> °	
Ride Height: <u>5</u> mm	Anti-Roll Bar: \varnothing <u>1.3</u> mm
Down Stop: <u>5.8</u> mm	

FF Arm Insert

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

FF Arm Mount

- #3 (+2 mm)
- #2 (kit 0 mm)
- #1 (-2 mm)

FR Arm Mount

- #3 (+2 mm)
- #2 (kit 0 mm)
- #1 (-2 mm)

FR Arm Insert

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

RR Arm Mount

- #3 (+2 mm)
- #2 (kit 0 mm)
- #1 (-2 mm)

RR Arm Insert

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

REAR SUSPENSION	
Track Width: _____ mm	<input checked="" type="checkbox"/> Gear Diff <u>3'000</u> wt
Toe Angle: _____ °	
Camber: <u>1.5</u> °	
Ride Height: <u>5.1</u> mm	
Down Stop: <u>4.8</u> mm	Anti-Roll Bar: \varnothing <u>1.2</u> mm

RF Arm Insert

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

RF Arm Mount

- #3 (+2 mm)
- #2 (kit 0 mm)
- #1 (-2 mm)

RR Arm Mount

- #3 (+2 mm)
- #2 (kit 0 mm)
- #1 (-2 mm)

RR Arm Insert

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

Motor Position:

- Inside (0mm)
- Outside (1mm)

Chassis:

- 2.3 mm
- 2.5 mm
- Aluminum

Upper Deck:


- 2 mm
- 2.3 mm
- 2.5 mm

ELECTRONICS
Servo: <u>Sanwa</u>
ESC: <u>ETS Combo</u>
Battery: <u>LRP 5800</u>

DRIVE RATIO
Spur $\frac{100}{38} \times 1.9 =$ <u>5.00</u>

MOTOR
Brand: <u>ETS Combo</u>
Turns: <u>13.5</u>
Timing: _____

TIRES
Insert: <u>Volante V5</u>
Wheel: <u>Volante V5</u>
Shore/deg: <u>28</u>
Compound: _____
Tire Temp: _____
Tire additive: <u>ETS "Hudy"</u>
Treated Area



ESC
Punch: _____
Initial Brake: _____
Drag Brake: _____
<input type="checkbox"/> ESC Timing <input type="checkbox"/> Turbo Timing

SHOCKS	
	Hole Size: <u>F 1.1</u> <u>R 1.1</u>
	Holes In Piston: <u>F 3</u> <u>R 3</u>
	Shock Oil WT: <u>F 400</u> <u>R 400</u>
	Shock Springs: <u>F Yok Blue</u> <u>R Yok Blue</u>
	Shock Rebound: <u>F 20%</u> <u>R 20%</u>
	Bladder Note: _____
	Thread Length: F _____ R _____
	Shock Length: F _____ R _____

BODY	
Body Position: _____	Body: <u>Protoform Speed 6 LW</u>
	Wing Height: _____
	Wing Position: _____