

TRACK CONDITIONS

Type: Carpet Asphalt Size: Open Med. Tight
 Place: Indoor Outdoor Traction: High Med. Low
 Surface: Smooth Med. Bumpy Track Temp/Air Temp: 25 / 23
 Note: Understeer + 4-wheel sliding

FRONT SUSPENSION

Track Width: _____ mm Gear Diff _____ wt
 Toe Angle: 1,0 ° One Way
 Caster: 4 ° Spool
 Camber: 2,0 °
 Ride Height: 5,4 mm Anti-Roll Bar: \varnothing 1,3 mm
 Down Stop: 6 mm

Shim: 1 mm
 Shim: 0 mm
 Hex Adapter: std
 Diff. High Low
 Shim: 1 mm
 Shim: 2 mm
 Shim: 0,1 mm
 Shim: 1 mm
 Shim: 0 mm

FF Arm Insert
 +0.4 mm
 +0.2 mm
 0 mm
 -0.2 mm
 -0.4 mm

FF Arm Mount
 #3 (+2 mm)
 #2 (kit 0 mm)
 #1 (-2 mm)

FR Arm Mount
 #3 (+2 mm)
 #2 (kit 0 mm)
 #1 (-2 mm)

FR Arm Insert
 +0.4 mm
 +0.2 mm
 0 mm
 -0.2 mm
 -0.4 mm

REAR SUSPENSION

Track Width: _____ mm Gear Diff 1000 wt
 Toe Angle: 2,2 °
 Camber: 1,8 °
 Ride Height: 5,6 mm
 Down Stop: 5 mm Anti-Roll Bar: \varnothing 1,2 mm

Shim: 3 mm
 Shim: 0 mm
 Hex Adapter: std
 Diff. High Low
 Shim: 1 mm
 Shim: 0,1 mm
 Shim: 1,75 mm
 Shim: 0,1 mm

RF Arm Insert
 +0.4 mm
 +0.2 mm
 0 mm
 -0.2 mm
 -0.4 mm

RF Arm Mount
 #3 (+2 mm)
 #2 (kit 0 mm)
 #1 (-2 mm)

RR Arm Mount
 #3 (+2 mm)
 #2 (kit 0 mm)
 #1 (-2 mm)

RR Arm Insert
 +0.4 mm
 +0.2 mm
 0 mm
 -0.2 mm
 -0.4 mm

Motor Position:
 Inside (0mm)
 Outside (1mm)
 _____ mm

Chassis: 2.3 mm 2.5 mm Aluminum

Upper Deck: 2 mm 2.3 mm 2.5 mm

3D Flex
 Fixed Post

ELECTRONICS

Servo: HRC
 ESC: fleta euro
 Battery: LRP 5800

DRIVE RATIO

Spur 76 T
 Pinion 36 T $\times 1.9 =$ 4.01

MOTOR

Brand: MuchMore
 Turns: 13,5
 Timing: 0

TIRES

Insert: _____
 Wheel: Sorex32
 Shore/deg: _____
 Compound: _____
 Tire Temp: 55
 Tire additive: HRC 6001
 Treated Area

ESC

Punch: 12
 Initial Brake: drag
 Drag Brake: 0
 ESC Timing Turbo Timing
blinky

FL FR RL RR

SHOCKS

Hole Size: F _____ R _____
 Holes In Piston: F 3 R 3
 Shock Oil WT: F 400 R 450
 Shock Springs: F P2,8 R L2,9
 Shock Rebound: F 3mm R 3mm
 Bladder Note: std
 Thread Length: F _____ R _____
 Shock Length: F _____ R _____

BODY

Body Position: 5mm Body: PF LTC 2.0
 Wing Height: _____
 Wing Position: 10mm