

SETUP SHEET



TRACK CONDITIONS						
Type:	<input type="checkbox"/> Carpet	<input checked="" type="checkbox"/> Asphalt	Size:	<input checked="" type="checkbox"/> Open	<input type="checkbox"/> Med.	<input type="checkbox"/> Tight
Place:	<input type="checkbox"/> Indoor	<input checked="" type="checkbox"/> Outdoor	Traction:	<input type="checkbox"/> High	<input checked="" type="checkbox"/> Med.	<input type="checkbox"/> Low
Surface:	<input checked="" type="checkbox"/> Smooth	<input type="checkbox"/> Med.	<input type="checkbox"/> Bumpy	Track Temp/Air Temp: <u>25</u> / <u>25</u>		
Note: _____						

FRONT SUSPENSION	
Track Width: _____ mm	<input checked="" type="checkbox"/> Gear Diff <u>Putty</u> wt
Toe Angle: <u>+0.5</u> °	<input type="checkbox"/> One Way
Caster: <u>4</u> °	<input type="checkbox"/> Spool
Camber: <u>1.5</u> °	
Ride Height: <u>5.0</u> mm	Anti-Roll Bar: \varnothing <u>1.3</u> mm
Down Stop: <u>6.0</u> mm	

Shim: 1 mm

Hex Adapter: -

Diff. High Low

Shim: 0 mm

Shim: 2 mm

Shim: 1 mm

Shim: 0.25 mm

Shim: 0.25 mm

Shim: 0.25 mm

Shim: 0.25 mm

FF Arm Insert

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

FF Arm Mount

- #3 (+2 mm)
- #2 (kit 0 mm)
- #1 (-2 mm)

FR Arm Mount

- #3 (+2 mm)
- #2 (kit 0 mm)
- #1 (-2 mm)

FR Arm Insert

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

REAR SUSPENSION	
Track Width: _____ mm	<input checked="" type="checkbox"/> Gear Diff <u>3000</u> wt
Toe Angle: _____ °	
Camber: <u>1.0</u> °	
Ride Height: <u>5.2</u> mm	
Down Stop: <u>4.8</u> mm	Anti-Roll Bar: \varnothing <u>1.2</u> mm

Shim: 4 mm

Shim: 1 mm

Hex Adapter: -

Diff. High Low

Shim: 1 mm

Shim: 1.75 mm

Shim: 0.25 mm

Shim: 0.25 mm

RF Arm Insert

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

RF Arm Mount

- #3 (+2 mm)
- #2 (kit 0 mm)
- #1 (-2 mm)

RR Arm Mount

- #3 (+2 mm)
- #2 (kit 0 mm)
- #1 (-2 mm)

RR Arm Insert

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

Motor Position:

- Inside (0mm)
- Outside (1mm)
- _____ mm

Chassis: 2.3 mm 2.5 mm Aluminum

Upper Deck: 2 mm 2.3 mm 2.5 mm

3D Flex Fixed Post


ELECTRONICS
Servo: <u>HRC</u>
ESC: <u>Much More</u>
Battery: <u>Much More</u>

MOTOR
Brand: <u>Much More</u>
Turns: <u>13.5</u>
Timing: <u>Fixed</u>

ESC
Punch: <u>Blinky</u>
Initial Brake: _____
Drag Brake: <u>0</u>
<input type="checkbox"/> ESC Timing <input type="checkbox"/> Turbo Timing

DRIVE RATIO
Spur <u>74</u> T
Pinion <u>31</u> T
$\times 1.9 =$ <u>4.54</u>

TIRES
Insert: <u>Volante 36</u>
Wheel: _____
Shore/deg: _____
Compound: _____
Tire Temp: _____
Tire additive: <u>HRC 6002 (20min.)</u>
Treated Area



SHOCKS
Hole Size: <u>F std</u> <u>R std</u>
Holes In Piston: <u>F 3</u> <u>R 3</u>
Shock Oil WT: <u>F 400</u> <u>R 350</u>
Shock Springs: <u>F Hpi Silver</u> <u>R Hpi Blue</u>
Shock Rebound: <u>F</u> <u>R</u>
Bladder Note: _____
Thread Length: <u>F</u> <u>R</u>
Shock Length: <u>F</u> <u>R</u>

BODY
Body Position: _____
Body: <u>LTC2.0</u>
Wing Height: _____
Wing Position: _____