

SETUP SHEET



TRACK CONDITIONS						
Type:	<input type="checkbox"/> Carpet	<input checked="" type="checkbox"/> Asphalt	Size:	<input checked="" type="checkbox"/> Open	<input type="checkbox"/> Med.	<input type="checkbox"/> Tight
Place:	<input type="checkbox"/> Indoor	<input checked="" type="checkbox"/> Outdoor	Traction:	<input type="checkbox"/> High	<input checked="" type="checkbox"/> Med.	<input type="checkbox"/> Low
Surface:	<input checked="" type="checkbox"/> Smooth	<input type="checkbox"/> Med.	<input type="checkbox"/> Bumpy	Track Temp/Air Temp: <u>25</u> / <u>25</u>		
Note: _____						

FRONT SUSPENSION	
Track Width: _____ mm	<input type="checkbox"/> Gear Diff _____ wt
Toe Angle: <u>+0.5</u> °	<input type="checkbox"/> One Way
Caster: <u>4</u> °	<input checked="" type="checkbox"/> Spool
Camber: <u>1.5</u> °	
Ride Height: <u>5.0</u> mm	Anti-Roll Bar: \varnothing <u>1.3</u> mm
Down Stop: <u>5.8</u> mm	

FF Arm Insert: +0.4 mm, +0.2 mm, 0 mm, -0.2 mm, -0.4 mm

FF Arm Mount: #3 (+2 mm), #2 (kit 0 mm), #1 (-2 mm)

FR Arm Mount: #3 (+2 mm), #2 (kit 0 mm), #1 (-2 mm)

FR Arm Insert: +0.4 mm, +0.2 mm, 0 mm, -0.2 mm, -0.4 mm

Shim: 1 mm, 1 mm, 0 mm, 1 mm, 1 mm, 0.25 mm, 0.10 mm

Hex Adapter: -

Diff. High, Low

REAR SUSPENSION	
Track Width: _____ mm	<input checked="" type="checkbox"/> Gear Diff <u>1000</u> wt
Toe Angle: <u>3.0</u> °	
Camber: <u>1.2</u> °	
Ride Height: <u>5.2</u> mm	
Down Stop: <u>4.5</u> mm	Anti-Roll Bar: \varnothing <u>1.2</u> mm

RF Arm Insert: +0.4 mm, +0.2 mm, 0 mm, -0.2 mm, -0.4 mm

RF Arm Mount: #3 (+2 mm), #2 (kit 0 mm), #1 (-2 mm)

RR Arm Mount: #3 (+2 mm), #2 (kit 0 mm), #1 (-2 mm)

RR Arm Insert: +0.4 mm, +0.2 mm, 0 mm, -0.2 mm, -0.4 mm

Shim: 4 mm, 1 mm, 1 mm, 1.75 mm, 0.25 mm

Hex Adapter: -

Diff. High, Low

Motor Position: Inside (0mm), Outside (1mm)

Chassis: 2.3 mm, 2.5 mm, Aluminum

Upper Deck: 2 mm, 2.3 mm, 2.5 mm


3D Flex, Fixed Post

ELECTRONICS
Servo: <u>HRC</u>
ESC: <u>Much More</u>
Battery: <u>Much More</u>

DRIVE RATIO
Spur <u>74</u> T
Pinion <u>31</u> T $\times 1.9 =$ <u>4.54</u>

MOTOR
Brand: <u>Much More</u>
Turns: <u>13.5</u>
Timing: <u>Fixed</u>

TIRES
Insert: <u>Volante 36</u>
Wheel: _____
Shore/deg: _____
Compound: _____
Tire Temp: _____
Tire additive: <u>HRC 6002 (20min.)</u>
Treated Area



SHOCKS
Hole Size: <u>F std</u> <u>R std</u>
Holes In Piston: <u>F 3</u> <u>R 3</u>
Shock Oil WT: <u>F 400</u> <u>R 350</u>
Shock Springs: <u>F Hpi Silver</u> <u>R Hpi Blue</u>
Shock Rebound: <u>F</u> <u>R</u>
Bladder Note: _____
Thread Length: <u>F</u> <u>R</u>
Shock Length: <u>F</u> <u>R</u>

ESC
Punch: <u>Blinky</u>
Initial Brake: _____
Drag Brake: <u>0</u>
<input type="checkbox"/> ESC Timing <input type="checkbox"/> Turbo Timing

BODY	
Body Position: _____	Body: <u>LTC2.0</u>
	Wing Height: _____
	Wing Position: _____