

TRACK CONDITIONS			
Type :	<input type="checkbox"/> Carpet	<input checked="" type="checkbox"/> Asphalt	Size: <input type="checkbox"/> Open <input checked="" type="checkbox"/> Med. <input type="checkbox"/> Tight
Place :	<input type="checkbox"/> Indoor	<input checked="" type="checkbox"/> Outdoor	Traction: <input type="checkbox"/> High <input checked="" type="checkbox"/> Med. <input type="checkbox"/> Low
Surface:	<input type="checkbox"/> Smooth	<input checked="" type="checkbox"/> Med. <input type="checkbox"/> Bumpy	Track Temp/Air Temp: _____ / _____
Note: _____			

### FRONT SUSPENSION

Track Width: \_\_\_\_\_ mm  Gear Diff \_\_\_\_\_ wt

Toe Angle: 0.5 °  One Way

Caster: 4 °  Spool

Camber: 1.8 °

Ride Height: 5.2 mm Anti-Roll Bar:  $\varnothing$  1.3 mm

Down Stop: 5.1 (30.8 / axle) mm

Shim: 1 mm

Shim: 0.75 mm

Hex Adapter: Kit

Diff.  High  Low

Shim: 2 mm

Shim: 0.5 mm

Shim: 1 mm

Shim: 0.9 mm

**FF Arm Insert**

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

**FF Arm Mount**

- #3 (+2 mm)
- #2 (kit 0 mm)
- #1 (-2 mm)

**FP Arm Mount**

- #3 (+2 mm)
- #2 (kit 0 mm)
- #1 (-2 mm)

**FP Arm Insert**

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

### REAR SUSPENSION

Track Width: \_\_\_\_\_ mm  Gear Diff 2000 wt

Toe Angle: 3 °

Camber: 1.8 °

Ride Height: 5.4 mm

Down Stop: 4.8 (30.7 / axle) mm Anti-Roll Bar:  $\varnothing$  1.3 mm

Shim: 4 mm

Shim: 1.5 mm

Hex Adapter: Kit

Diff.  High  Low

Shim: 1.5 mm

Shim: 0.9 mm

Shim: 1.5 mm

Shim: 0.9 mm

**RF Arm Insert**

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

**RF Arm Mount**

- #3 (+2 mm)
- #2 (kit 0 mm)
- #1 (-2 mm)

**RP Arm Mount**

- #3 (+2 mm)
- #2 (kit 0 mm)
- #1 (-2 mm)

**RR Arm Insert**

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

Motor Position :

- Inside (0mm)
- Outside (1mm)

Chassis:  2.3 mm  2.5 mm  Aluminum

Upper Deck:  2 mm  2.3 mm  2.5 mm

### ELECTRONICS

Servo: \_\_\_\_\_

ESC: \_\_\_\_\_

Battery: \_\_\_\_\_

### DRIVE RATIO

Spur  $\frac{T}{T} \times 1.9 =$  \_\_\_\_\_

Pinion \_\_\_\_\_

### MOTOR

Brand: \_\_\_\_\_

Turns: \_\_\_\_\_

Timing: \_\_\_\_\_

### TIRES

Insert : \_\_\_\_\_

Wheel: \_\_\_\_\_

Shore/deg: Ride Rex34

Compound: \_\_\_\_\_

Tire Temp: 65°

Tire additive: CS High Grip

Treated Area

### ESC

Punch: \_\_\_\_\_

Initial Brake: \_\_\_\_\_

Drag Brake: \_\_\_\_\_

ESC Timing  Turbo Timing

FL FR RL RR

### SHOCKS

Hole Size: F 1.1 R 1.1

Holes In Piston: F 3 R 3

Shock Oil WT: F 450 R 400

Shock Springs: F Ride Green R Ride Green

Shock Rebound: F 2mm R 2mm

Bladder Note: \_\_\_\_\_

Thread Length: F R

Shock Length : F R

### BODY

Body Position: 0mm Body: Protoform Dodge Dart

Wing Height: Max

Wing Position: +10mm