

SETUP SHEET



TRACK CONDITIONS						
Type:	<input checked="" type="checkbox"/> Carpet	<input type="checkbox"/> Asphalt	Size:	<input type="checkbox"/> Open	<input checked="" type="checkbox"/> Med.	<input type="checkbox"/> Tight
Place:	<input checked="" type="checkbox"/> Indoor	<input type="checkbox"/> Outdoor	Traction:	<input checked="" type="checkbox"/> High	<input type="checkbox"/> Med.	<input type="checkbox"/> Low
Surface:	<input checked="" type="checkbox"/> Smooth	<input type="checkbox"/> Med.	<input type="checkbox"/> Bumpy	Track Temp/Air Temp: _____ / _____		
Note: _____						

FRONT SUSPENSION	
Track Width: _____ mm	<input type="checkbox"/> Gear Diff _____ wt
Toe Angle: <u>0.5</u> °	<input type="checkbox"/> One Way
Caster: <u>4</u> °	<input checked="" type="checkbox"/> Spool
Camber: <u>1.5</u> °	
Ride Height: <u>5.2</u> mm	Anti-Roll Bar: \varnothing <u>1.3</u> mm
Down Stop: <u>5.5 (31.2/Axle)</u> mm	

Shim: 1 mm

Shim: 0.5 mm

Hex Adapter: -0.75

Diff. High Low

Shim: 2 mm

Shim: 0 mm

Shim: 1 mm

Shim: 1 mm

Shim: 1 mm

Shim: 1 mm

Shim: 1 mm

FF Arm Insert

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

FF Arm Mount

- #3 (+2 mm)
- #2 (kit 0 mm)
- #1 (-2 mm)

FR Arm Mount

- #3 (+2 mm)
- #2 (kit 0 mm)
- #1 (-2 mm)

FR Arm Insert

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

REAR SUSPENSION	
Track Width: _____ mm	<input checked="" type="checkbox"/> Gear Diff <u>Yok Dot 6</u> wt
Toe Angle: <u>2.7</u> °	
Camber: <u>1.5</u> °	
Ride Height: <u>5.4</u> mm	
Down Stop: <u>5.5 (31.4/Axle)</u> mm	Anti-Roll Bar: \varnothing <u>1.3</u> mm

Shim: 4 mm

Shim: 1.25 mm

Hex Adapter: -0.75

Diff. High Low

Shim: 1.5 mm

Shim: 1 mm

Shim: 1.5 mm

Shim: 1 mm

RF Arm Insert

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

RF Arm Mount

- #3 (+2 mm)
- #2 (kit 0 mm)
- #1 (-2 mm)

RR Arm Mount

- #3 (+2 mm)
- #2 (kit 0 mm)
- #1 (-2 mm)

RR Arm Insert

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

Motor Position:

- Inside (0mm)
- Outside (1mm)

Chassis: 2.3 mm 2.5 mm Aluminum

Upper Deck: 2 mm 2.3 mm 2.5 mm


3D Flex Fixed Post

ELECTRONICS
Servo: <u>Sanwa SRG-BLS</u>
ESC: <u>HW V3.1</u>
Battery: <u>Reedy 7000</u>

DRIVE RATIO
Spur <u>84</u> T
Pinion <u>20</u> T
$\times 1.9 =$ <u>7.98</u>

MOTOR
Brand: <u>Reedy Mach 2</u>
Turns: <u>4.5</u>
Timing: <u>25°</u>

TIRES
Insert: _____
Wheel: _____
Shore/deg: <u>Ride Rex32</u>
Compound: _____
Tire Temp: _____
Tire additive: <u>Hudy ETS</u>
Treated Area



ESC
Punch: <u>4/6 Switch @ 66</u>
Initial Brake: <u>=DB</u>
Drag Brake: <u>5</u>
<input checked="" type="checkbox"/> ESC Timing <input checked="" type="checkbox"/> Turbo Timing
<u>15 Boost / 32 Turbo / 0.15s / 24eng / 24dis</u>

SHOCKS
Hole Size: <u>F 1.1</u> <u>R 1.1</u>
Holes In Piston: <u>F 3</u> <u>R 3</u>
Shock Oil WT: <u>F UR 400</u> <u>R UR 400</u>
Shock Springs: <u>F HPI Silver</u> <u>R HPI Silver</u>
Shock Rebound: <u>F</u> <u>R</u>
Bladder Note: _____
Thread Length: <u>F</u> <u>R</u>
Shock Length: <u>F</u> <u>R</u>

BODY	
Body Position: <u>+5mm</u>	Body: <u>Protoform LTC-R</u>
	Wing Height: <u>Max</u>
	Wing Position: <u>+10mm</u>