

SETUP SHEET



TRACK CONDITIONS			
Type :	<input type="checkbox"/> Carpet	<input checked="" type="checkbox"/> Asphalt	Size: <input checked="" type="checkbox"/> Open <input type="checkbox"/> Med. <input type="checkbox"/> Tight
Place :	<input type="checkbox"/> Indoor	<input checked="" type="checkbox"/> Outdoor	Traction: <input type="checkbox"/> High <input checked="" type="checkbox"/> Med. <input type="checkbox"/> Low
Surface:	<input type="checkbox"/> Smooth <input type="checkbox"/> Med.	<input checked="" type="checkbox"/> Bumpy	Track Temp/Air Temp: <u>~20</u> / <u>~30</u>
Note: _____			

FRONT SUSPENSION	
Track Width: _____ mm	<input type="checkbox"/> Gear Diff _____ wt
Toe Angle: <u>0.5</u> °	<input type="checkbox"/> One Way
Caster: <u>4</u> °	<input checked="" type="checkbox"/> Spool
Camber: <u>1.75R / 1.5L</u> °	Anti-Roll Bar: \varnothing <u>1.3</u> mm
Ride Height: <u>5.0</u> mm	Down Stop: <u>4.5 (30.2/Axle)</u> mm

FF Arm Insert

 +0.4 mm
 +0.2 mm
 0 mm
 -0.2 mm
 -0.4 mm

FF Arm Mount

 #3 (+2 mm)
 #2 (kit 0 mm)
 #1 (-2 mm)

FR Arm Mount

 #3 (+2 mm)
 #2 (kit 0 mm)
 #1 (-2 mm)

FR Arm Insert

 +0.4 mm
 +0.2 mm
 0 mm
 -0.2 mm
 -0.4 mm

RR Arm Mount

 #3 (+2 mm)
 #2 (kit 0 mm)
 #1 (-2 mm)

RR Arm Insert

 +0.4 mm
 +0.2 mm
 0 mm
 -0.2 mm
 -0.4 mm

REAR SUSPENSION	
Track Width: _____ mm	<input checked="" type="checkbox"/> Gear Diff <u>Yok Dot 5</u> wt
Toe Angle: <u>2.7</u> °	Camber: <u>1.75R / 1.5L</u> °
Ride Height: <u>5.2</u> mm	Down Stop: <u>4.5 (30.4/Axle)</u> mm
Anti-Roll Bar: \varnothing <u>1.3</u> mm	

RF Arm Insert

 +0.4 mm
 +0.2 mm
 0 mm
 -0.2 mm
 -0.4 mm

RF Arm Mount

 #3 (+2 mm)
 #2 (kit 0 mm)
 #1 (-2 mm)

RR Arm Mount

 #3 (+2 mm)
 #2 (kit 0 mm)
 #1 (-2 mm)

RR Arm Insert

 +0.4 mm
 +0.2 mm
 0 mm
 -0.2 mm
 -0.4 mm

Motor Position :

 Inside (0mm)
 Outside (1mm)

Chassis: 2.3 mm 2.5 mm Aluminum


Upper Deck: 2 mm 2.3 mm 2.5 mm

ELECTRONICS
Servo: <u>Sanwa SRG-BLS</u>
ESC: <u>HW V3.1</u>
Battery: <u>Reedy 7000</u>

DRIVE RATIO
Spur <u>84</u> T
Pinion <u>22</u> T $\times 1.9 =$ <u>7.25</u>

MOTOR
Brand: <u>Reedy Mach 2</u>
Turns: <u>5.0</u>
Timing: <u>25°</u>

TIRES
Insert : _____
Wheel: _____
Shore/deg: <u>Ride Rex34</u>
Compound: _____
Tire Temp: <u>65° / 15mins</u>
Tire additive: <u>Hudy ETS</u>
Treated Area



ESC
Punch: <u>12/16 Switch @ 66</u>
Initial Brake: <u>=DB</u>
Drag Brake: <u>4</u>
<input checked="" type="checkbox"/> ESC Timing <input checked="" type="checkbox"/> Turbo Timing
<u>25 Boost / 32 Turbo / 0.15s / 18eng / 24dis</u>

SHOCKS
Hole Size: <u>F 1.1</u> <u>R 1.1</u>
Holes In Piston: <u>F 3</u> <u>R 3</u>
Shock Oil WT: <u>F UR 400</u> <u>R UR 400</u>
Shock Springs: <u>F Ride Purple</u> <u>R Hara Purple</u>
Shock Rebound: <u>F 2mm</u> <u>R 2mm</u>
Bladder Note: <u>HPI Silver in qualifications</u>
Thread Length: F _____ R _____
Shock Length : F _____ R _____

BODY	
Body Position: <u>0mm</u>	Body: <u>Protoform Dodge Dart</u>
Wing Height: <u>Max</u>	Wing Position: <u>+10mm</u>