

## SETUP SHEET



TRACK CONDITIONS						
Type:	<input type="checkbox"/> Carpet	<input checked="" type="checkbox"/> Asphalt	Size:	<input checked="" type="checkbox"/> Open	<input type="checkbox"/> Med.	<input type="checkbox"/> Tight
Place:	<input type="checkbox"/> Indoor	<input checked="" type="checkbox"/> Outdoor	Traction:	<input type="checkbox"/> High	<input checked="" type="checkbox"/> Med.	<input type="checkbox"/> Low
Surface:	<input type="checkbox"/> Smooth	<input checked="" type="checkbox"/> Med.	<input type="checkbox"/> Bumpy	Track Temp/Air Temp: _____ / <u>18</u>		
Note: _____						

FRONT SUSPENSION	
Track Width: _____ mm	<input type="checkbox"/> Gear Diff _____ wt
Toe Angle: <u>2</u> °	<input type="checkbox"/> One Way
Caster: <u>4</u> °	<input checked="" type="checkbox"/> Spool
Camber: <u>2</u> °	
Ride Height: <u>5.4</u> mm	Anti-Roll Bar: $\varnothing$ <u>1.3</u> mm
Down Stop: <u>5.5</u> mm	

**FF Arm Insert**

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

**FF Arm Mount**

- #3 (+2 mm)
- #2 (kit 0 mm)
- #1 (-2 mm)

**FR Arm Mount**

- #3 (+2 mm)
- #2 (kit 0 mm)
- #1 (-2 mm)

**FR Arm Insert**

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

**RR Arm Mount**

- #3 (+2 mm)
- #2 (kit 0 mm)
- #1 (-2 mm)

**RR Arm Insert**

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

REAR SUSPENSION	
Track Width: _____ mm	<input checked="" type="checkbox"/> Gear Diff <u>7000</u> wt
Toe Angle: <u>2.2</u> °	
Camber: <u>2</u> °	
Ride Height: <u>5.6</u> mm	
Down Stop: <u>4.5</u> mm	Anti-Roll Bar: $\varnothing$ <u>1.2</u> mm

**RF Arm Insert**

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

**RF Arm Mount**

- #3 (+2 mm)
- #2 (kit 0 mm)
- #1 (-2 mm)

**RR Arm Mount**

- #3 (+2 mm)
- #2 (kit 0 mm)
- #1 (-2 mm)

**RR Arm Insert**

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

**Motor Position:**

- Inside (0mm)
- Outside (1mm)

**Chassis:**  2.3 mm  2.5 mm  Aluminum


**Upper Deck:**  2 mm  2.3 mm  2.5 mm

ELECTRONICS
Servo: <u>HRC</u>
ESC: <u>Orion</u>
Battery: <u>Orion</u>

DRIVE RATIO
Spur $\frac{81}{20} T \times 1.9 =$ <u>7.70</u>
Pinion

MOTOR
Brand: <u>Orion</u>
Turns: <u>4.5</u>
Timing: <u>0</u>

TIRES
Insert: <u>Panaracer VX40</u>
Wheel: _____
Shore/deg: _____
Compound: _____
Tire Temp: <u>55</u>
Tire additive: <u>MR33 + Carpet 2</u>
Treated Area



ESC
Punch: <u>4</u>
Initial Brake: _____
Drag Brake: <u>7%</u>
<input checked="" type="checkbox"/> ESC Timing <input checked="" type="checkbox"/> Turbo Timing

SHOCKS
Hole Size: <u>F 1.1</u> <u>R 1.1</u>
Holes In Piston: <u>F 3</u> <u>R 3</u>
Shock Oil WT: <u>F 450</u> <u>R 450</u>
Shock Springs: <u>F HPI Silver</u> <u>R HPI Silver</u>
Shock Rebound: <u>F 3mm</u> <u>R 3mm</u>
Bladder Note: _____
Thread Length: <u>F</u> <u>R</u>
Shock Length: <u>F</u> <u>R</u>

BODY	
Body Position: <u>+3mm</u>	Body: <u>Protoform LTCR</u>
	Wing Height: <u>-1mm</u>
	Wing Position: <u>Central</u>