

# TEKIN

# RS SETUP SHEET

RS & RS PRO

DRIVER: Donny Lia  
VEHICLE: Speed Merchant Rev 5  
TRACK: IIC 2009 Vegas Race  
SURFACE: Carpet  
TRACTION: LOW  MED  HIGH

MOTOR: Tekin Redline 4.5  
ENDBELL TIMING: 0  
ROTOR: 12.5  
GEARING: n/a  
BATTERY: SMC 1s Lipo

### ESC SETTINGS:

FILL IN LED LOCATION AND WRITE IN SETTING NUMBER

The ESC settings panel features a central control unit with a 'MODE' button on the left and an 'INCR' button on the right. Between them are seven LED indicators labeled DB, BS, LM, NW, TP, MT, and VC. Lines connect these LEDs to various settings: DB to Drag Brake, BS to Brake Strength, LM to Limiter, NW to Neutral Width, TP to Throttle Profile, MT to Motor Type, and VC to Voltage Cutoff. Each setting is represented by a digital readout (DRO) with a bar graph and a numerical value.

Firmware Version:	200		
DRAG BRAKE	10		
BRAKE STRENGTH	95		
LIMITER	84		
NEUTRAL WIDTH	15		
VOLTAGE CUTOFF	1		
MOTOR TYPE	1		
THROTTLE PROFILE	3		
<b>HOTWIRE SOFTWARE</b>	3.25		
DUAL MODE	<input checked="" type="checkbox"/>	SENSORED	<input type="checkbox"/>
TIMING ADVANCE:	90		
REVERSE STRENGTH:	n/a		
PUSH CONTROL:	off		
TIMING BOOST:	n/a		
TURBO BOOST:	0	TURBO DELAY:	0

### NOTES:

Motor temp 135'f.

---

---

---

---