

"Scythe" Setup Sheet for _____

Name **Jimmy maddison** Date **November** Humidity _____ % Air Temp. **15** °C
 Track **Grimsby awesome high traction carpet set up** Track Condition bad 1 2 3 **4** 5 good Track Temp. _____ °C

Front Suspension

Camber Angle	1 °
Castor	4 °
Ride Height	5 mm
Drop	5.0 mm
FR. Drive	One-way
Stabilizer Bar	∅ 1.6
Stick out	2 mm
Toe Angle	0 °
Notes	

Sus. Mount	F 1.5	Sus. Mount Spacer	F 1.5 mm
	R 0.0		R 1.5 mm

Shock Absorber

	Front	rear
	2 Holes	2 Holes
Piston & Holes	1.2mm	1.2mm
Oil	50	40
Spring	17.5	14.5lb
Diaphragm	Standard	Standard
Form		
Other	70% rebound	
	O-ring in top	

Rear Suspension

Camber Angle	1.5 °
Ride Height	5.2 mm
Drop	4 mm
Stabilizer Bar	∅
Stick out	mm
Upright Spacer	F 2 mm
	R .75 mm
Notes	

Sus. Mount	F 0.0	Sus. Mount Spacer	F 1.5 mm
	R 3.0		R 1.5 mm

Tire

	Front	rear
Brand	Vtech-24	Vtech-24
Insert	Lrp white	
Wheel	vtech	vtech
Additive	paragon	
Spreaded Area		

Ackermann

Ex.Front
 Rear
 Mid
 Front
 Ex.Rear

1
 2

Radio

Transmitter **ko**

Receiver **ko**

Servo **Futaba 9550**

ESC **NOVAK**

Power Source

Motor **Almighty** Battery **Almighty**

Rotor **27t monster**

Brush **meteor**

Spring **220g**

Timing **N/A**

Gear Ratio

Spur **104**

Pinion **30** ÷

2nd Reduction **x 2.200**

Over All Ratio

Body

Parma type M

Wing

std