

CAMBERLINK LOCATION

1

2

TOE

WHEEL HEX

SPACER

STABILIZER

CAMBER

STEERING SUPPORT

DOWNSTOP

UNDER HUB/ARM

Shock Position

Insert Position

DIFF

SOLID AXLE

GEAR DIFF

OIL

POSITION

OUTER DRIVE

SPRING STEEL

ALUMINIUM

PLASTIC

HIGH/LOW

SPACER

SUSPENSION MOUNT

SUSPENSION SHIM

FF

FR

FF MOUNT

INSERT

NARROW/WIDE

FR MOUNT TYPE

BRASS

SOLID

SPLIT

FRONT

CAMBERLINK LOCATION

1

2

WHEEL HEX

TOE

CAMBER

DOWNSTOP

UNDER HUB/ARM

Shock Position

Insert Position

DIFF

GEAR DIFF

OIL

POSITION

OUTER DRIVE

STEEL

ALUMINIUM

HIGH/LOW

SPACER

STABILIZER

SUSPENSION MOUNT

SUSPENSION SHIM

RF

RR

RR MOUNT

INSERT

NARROW/WIDE

RF MOUNT TYPE

BRASS

SOLID

SPLIT

REAR

SPACER

STEERING LOCK

SERVO HORN HEIGHT

BRAND

FLEX

GROUND CLEARANCE

WHEELBASE SETUP

GROUND CLEARANCE

FRONT SHOCK

PISTON

OIL

SPRING

OIL SEALER CAP

REBOUND

NOTES

REAR SHOCK

PISTON

OIL

SPRING

OIL SEALER CAP

REBOUND

NOTES

SHOCK SHIMS

TOWER

ARM

WEIGHT

SPACER

MOTOR MOUNT CENTER FLEX

CHASSIS

WEIGHT

V BRACE

SHOCK SHIMS

TOWER

ARM

WEIGHT

MOTOR

TIRE

TIRE ADDICTIVE

ESC

REMARKS

SPUR

TIRE INSERT

BODY

BATTERY

T

PITCH

WHEEL

WING

REMARKS

Amo - ProfEQ.com