

SETUP SHEET



SETUP

DRIVER	
DATE	
EVENT	
TRACK	

FRONT SETUP

SPRINGS			
DAMPING			
DYNAMIC CASTER	5	10	15
UPPER WISHBONE	forward	mid	back
FRONT RIDEHEIGHT	(3,0 mm)	(4,0 mm)	
	(3,5 mm)	(4,5 mm)	

BRACE			
CAMBER		deg	
SERVO POSITION	Flat	Angled	
OUTER BALL			
FRONT WIDTH	(166 mm)	(170 mm)	
	(168 mm)	(172 mm)	

REAR SETUP

T-BAR	Thin	Thick
T BAR BRAND	AE	CRC
REAR RIDEHEIGHT	(3,0 mm)	(4,0 mm)
	(3,5 mm)	(4,5 mm)

SHOCK SPRING		
SHOCK OIL	(WT)	
TUBE DAMPING		
REAR WIDTH	(166 mm)	(170 mm)
	(168 mm)	(172 mm)

TIRES

FRONT TYRE		(mm)
FRONT TIRE ADDITIVE		(%)
FRONT WHEEL		

REAR TYRE		(mm)
REAR TIRE ADDITIVE		(%)
REAR WHEEL		

MOTOR

MOTOR	(brand)	(turns)
TIMING		(mm)
ROTOR		(mm)

GEAR RATIO		(mm/rv)
PINION / SPUR	(teeth)	(teeth)
PITCH	(48 dp)	(64 dp)

BAT

BATTERY	
RECEIVER BATTERY	

CHARGER			
BATTERY POSITION	forward	mid	back

OTHER

ESC	
ESC PROGRAM	
CHASSIS	

RADIO	
SERVO	
BODYSHELL	

RACE DATA & NOTES

RACE RESULT	(Qual.)	(Final)	
POSITION IN MAINS	(F1)	(F2)	(F3)
FASTEST QUALIFYER	(Laps)	(Time)	
FASTEST LAP TIME	(Sec.)		

TRACK SURFACE			
COMPOSITION			
TRACTION	(Low)	(Med.)	(High)
TEMPERATURE			

NOTES

The Winning Design