

SETUP SHEET



SETUP

DRIVER	
DATE	
EVENT	
TRACK	

FRONT SETUP

SPRINGS					
DAMPING					
DYNAMIC CASTER	5	10	15		
UPPER WISHBONE	forward	mid	back		
FRONT RIDEHEIGHT	(3,0 mm)	(4,0 mm)			
	(3,5 mm)	(4,5 mm)			

BRACE				
CAMBER		deg		
SERVO POSITION	Flat	Angled		
OUTER BALL				
FRONT WIDTH	(166 mm)	(170 mm)		
	(168 mm)	(172 mm)		

REAR SETUP

SIDE SPRING	AE	CRC		
SPRING MOUNT POINT	IN	OUT		
TUBE DAMPING				
REAR RIDEHEIGHT	(3,0 mm)	(4,0 mm)		
	(3,5 mm)	(4,5 mm)		

SHOCK SPRING				
SHOCK OIL				(WT)
SHOCK BALL HIGHT	front	(mm)	rear	(mm)
REAR WIDTH	(166 mm)	(170 mm)		
	(168 mm)	(172 mm)		

TIRES

FRONT TYRE		(mm)
FRONT TIRE ADDITIVE		(%)
FRONT WHEEL		

REAR TYRE		(mm)
REAR TIRE ADDITIVE		(%)
REAR WHEEL		

MOTOR

MOTOR	(brand)	(turns)
TIMING		(mm)
ROTOR		(mm)

GEAR RATIO		(mm/rv)
PINION / SPUR	(teeth)	(teeth)
PITCH	(48 dp)	(64 dp)

BAT

BATTERY		
RECEIVER BATTERY		

CHARGER				
BATTERY POSITION	forward	mid	back	

OTHER

ESC		
ESC PROGRAM		
CHASSIS		

RADIO		
SERVO		
BODYSHELL		

RACE DATA & NOTES

RACE RESULT	(Qual.)	(Final)	
POSITION IN MAINS	(F1)	(F2)	(F3)
FASTEST QUALIFYER	(Laps)	(Time)	
FASTEST LAP TIME	(Sec.)		

TRACK SURFACE			
COMPOSITION			
TRACTION	(Low)	(Med.)	(High)
TEMPERATURE			

NOTES				