

Driver Marcos Fj Surface Asphalt (Indoor/Outdoor) Carpet Smooth Bumpy Track Temperature 89
 Date 05-11-19 Traction Low Medium High Dry Wet Result TQ/Win Air Temperature 95
 Track SS Race way Country USA Best Lap 12.8 Humidity _____ Remark _____

Front

Spacer 2mm, 1mm, 4, 3, 2, 1

Spacer mm, mm

C-Hub	Hex Offset	5 mm	5 mm
<input checked="" type="checkbox"/> M <input type="checkbox"/> H	Camber	2°	
Steering Block	Ride Height	5 mm	mm
<input checked="" type="checkbox"/> M <input type="checkbox"/> H	DownStop	5 mm	mm
Suspension Arm	Sway Bar	1.2 mm	mm
<input checked="" type="checkbox"/> M <input type="checkbox"/> H			

Rear

Spacer mm, mm

Rear Hub	Hex Offset	5 mm
<input type="checkbox"/> M <input type="checkbox"/> H	Camber	2°
Suspension Arm	Ride Height	5.2 mm
<input type="checkbox"/> M <input type="checkbox"/> H	DownStop	4 mm
	Sway Bar	1.1 mm

Optional

Spacer 1 mm, 1 mm, 0 mm

On-Power Control System

Steering Block M H

Suspension Arm M H

Front Toe Out 1.5°

Lower Arm Spacer 0 mm

Bump Steering Spacer 2 mm

Shock Tower Spacer 2 mm

Link Spacer 1 mm

Weight g

TopDeck 2 mm

Wheelbase Spacer FF 1 mm, FR 1 mm

Rear Toe In 3°

Lower Arm Spacer 0 mm

Shock Tower Spacer 0 mm

Link Spacer 0 mm

Wheelbase Spacer RF 3 mm, RR 1 mm

Weight 101 g

Chassis Aluminium Carbon

Floating Steering Non-Floating Steering

Suspension Mount Setup

FF	FR	RF	RR
<input type="checkbox"/> I <input checked="" type="checkbox"/> 0.5	<input type="checkbox"/> I <input checked="" type="checkbox"/> 0.5	<input type="checkbox"/> I <input checked="" type="checkbox"/> 0.5	<input type="checkbox"/> I <input checked="" type="checkbox"/> 0.5
<input checked="" type="checkbox"/> Aluminium <input type="checkbox"/> Brass	<input checked="" type="checkbox"/> Aluminium <input type="checkbox"/> Brass	<input checked="" type="checkbox"/> Aluminium <input type="checkbox"/> Brass	<input checked="" type="checkbox"/> Aluminium <input type="checkbox"/> Brass
<input type="checkbox"/> Spill <input type="checkbox"/> Solid	<input checked="" type="checkbox"/> Spill <input type="checkbox"/> Solid	<input type="checkbox"/> Spill <input type="checkbox"/> Solid	<input type="checkbox"/> Spill <input type="checkbox"/> Solid

Center Line Flex Control

Turnbuckle Carbon Fiber None

Center Post Nut

Spacer mm

Lower Screw

Damper Setup

Front	Rear
Spring <u>Xray 2.5/2.8</u>	Spring <u>xray 2.6</u>
Oil <u>37.5wt</u>	Oil <u>37.5wt</u>
Rebound <u>0</u>	Rebound <u>0</u>
Piston <u>4holes</u>	Piston <u>4holes</u>
Length <u>10mm</u>	Length <u>10mm</u>
Foam Insert <input type="checkbox"/>	Foam Insert <input type="checkbox"/>
Hole In Cap <input type="checkbox"/>	Hole In Cap <input type="checkbox"/>

Transmission Setup

Front	Rear
Spool <u>Gear Diff</u>	Gear Diff
Oil _____	Oil <u>3k</u>
Weight _____ g	Weight <u>1.2 g</u>
Position <u>Low High</u>	Position <u>Low High</u>

Servo <u>Team Power</u>	Tires <u>GravityUSGT</u>
Esc <u>byWingXF</u>	Additive <u>RedDot</u>
Motor <u>Trinity 21.5</u>	Body <u>Venom</u>
Spur <u>48 p/</u>	T Rear Wing <u>stock</u>
Pinion <u>48 p/</u>	FDR <u>35</u>

Used 1mm shims under the top deck
 this set up worked very well in 17.5Expert with Solaris 36 tires and a Bitty JP8 HR.