

SET-UP SHEET

XRAY T4'14

RACE	GP3F		
TRACK	Longwy		
NAME	Anonymous		
CITY / COUNTRY	Nntes	France	
CONTACT	mathias.rascol@gmail.com		

DATE	15/01/2014	TEMPERATURE / °F or °C	AIR	TRACK
------	------------	------------------------	-----	-------

QUALIFYING POSITION	BEST LAPTIME /sec	FINAL POSITION	RACE LENGTH /minutes
18		18	

TRACK CONDITION	☒ CARPET	☐ ASPHALT	
☐ TECHNICAL	☒ MIXED	☐ FAST	
TRACTION	☐ LOW	☐ MEDIUM	☒ HIGH

FRONT	REAR
TRANSMISSION	

SOLID AXLE	☒ YES	BALL DIFFERENTIAL	☐ YES
SOLID ONE WAY DIFF.	☐ YES		
ONE WAY DIFFERENTIAL	☐ YES		

GEAR DIFFERENTIAL	☐ YES	GEAR DIFFERENTIAL	☒ YES
OIL		OIL	3000 /Cst

PINION / T	27	SPUR GEAR / T	114
FINAL DRIVE RATIO	4.22222222222222	ROLLOUT	0

FRONT	REAR
-------	------

2.5	XRAY SPRINGS	2.5
-----	--------------	-----

350	OIL / CST	350
-----	-----------	-----

	LENGTH /mm	
--	------------	--

	PRELOAD /mm	
--	-------------	--

5%	REBOUND %	5%
----	-----------	----

☐ YES ☒ NO	FOAM INSERTS	☐ YES ☒ NO
☐ YES ☒ NO	O-RING ON SHAFT	☐ YES ☒ NO

☐ 3 HOLES	PISTONS	☐ 3 HOLES
☒ 4 HOLES	1.0mm	☒ 4 HOLES
	1.1mm	
	1.2mm	
	OTHERS	

1.4	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.2
-----	--------------	---------------	--------------	-----

CPX	TIRES	CPX
-----	-------	-----

CPX	INSERTS	CPX
-----	---------	-----

LRP3	ADDITIVE	LP3
------	----------	-----

20	ADDITIVE TIMING	20
----	-----------------	----

FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT
TREATED AREA			

WHEELS			
S	M	H	
HARDNESS			

MOTOR	5.5	TIMING	
ROTOR		ARMATURE	

ESC	Nosram COMET	BATTERIES	Nosram 7200
-----	--------------	-----------	-------------

BODY	Speed6	WING	MR33
------	--------	------	------

☒ - APPLIED	S - SOFT	M - MEDIUM	H - HARD
---	----------	------------	----------

FRONT	REAR
CASTER 0° ☐ 2° ☐ 4° ☒ 6° ☐ SHIM 2 /mm WHEELBASE/mm 257 RIDE HEIGHT/mm 5	RIDE HEIGHT/mm 5.2

C-HUB M ☐ H ☒ ALU ☐ STEERING BLOCK M ☒ H ☐ ALU ☐ OFFSET STANDARD ☒	SHIM 2 /mm LONG 52mm ☒ SHORT 50mm ☐ SHIM 2 /mm LONG 52mm ☐ SHORT 50mm ☒ SHIM 2 /mm LONG 52mm ☐ SHORT 50mm ☒ SHIM 4 /mm LONG 52mm ☐ SHORT 50mm ☒ REAR HUB M ☐ H ☒ ALU ☐ OPTIONAL HUB OFFSET STANDARD ☒
--	--

FF ☐ 0.5 ☐ FR ☐ 0.5 ☐ RR ☐ 0.5 ☐ RF ☐ 0.5 ☐	ROLL CENTER ECCENTRIC BUSHINGS ☐ 0.5 ☐
--	---

TOE /deg. FINAL TOE IN OUTBOARD + INBOARD TOE 3 OUTBOARD TOE 0 TOE OUT 0.5 SHIM UNDER SHOCK SHIM 2.5 /mm ACKERMANN SHIM SHIM 1.5 /mm STEERING ARM STANDARD ☐ ALU ☒ ROLL CENTER UPPER CLAMP	SHIM UNDER SHOCK SHIM /mm ANTI ROLL BAR ROLL CENTER UPPER CLAMP
--	--

FRONT	REAR
2.5 CAMBER /deg. UPPER SHOCK POSITION FRONT ARM STANDARD (H) ☐ GRAPHITE (G) ☒ GRAPHITE PLATE YES ☐ NO ☒	2.5 REAR ARM STANDARD (H) ☐ GRAPHITE (G) ☒ GRAPHITE PLATE YES ☐ NO ☒

ECCENTER /mm STANDARD ☒ DIFF POSITION UP ☒ DOWN ☐ LOWER SUSP. BLOCK SOLID 1pcs ☒ SINGLE 2 pcs ☐	TOP DECK 2.0mm ☐ 1.6mm ☐ ALU STAND YES ☒ NO ☐
--	---

COMMENTS
