

SET-UP SHEET

XRAY T4

RACE	Uisp Italian Nats Indoor		
TRACK	Rc Landia		
NAME	Alessio Menicucci		
CITY / COUNTRY	Scandiano	Italy	
CONTACT	menicucci.a@libero.it		

DATE	19/03/2013	TEMPERATURE / °F or °C	AIR	TRACK
QUALIFYING POSITION	1	BEST LAPTIME /sec	13.0	FINAL POSITION
				1
				RACE LENGTH /minutes

TRACK CONDITION	☒ CARPET	☐ ASPHALT
	☐ TECHNICAL	☒ MIXED
TRACTION	☐ LOW	☐ MEDIUM
	☐ FAST	☐ HIGH

FRONT	REAR
TRANSMISSION	
SOLID AXLE ☒ YES	BALL DIFFERENTIAL ☐ YES
SOLID ONE WAY DIFF. ☐ YES	
ONE WAY DIFFERENTIAL ☐ YES	
GEAR DIFFERENTIAL ☐ YES	GEAR DIFFERENTIAL ☒ YES
OIL	OIL 3000 cst /Cst

PINION / T	24	SPUR GEAR / T	114
FINAL DRIVE RATIO	4.75	ROLLOUT	NaN

FRONT	REAR
2.5-2.8	XRAY SPRINGS
300	OIL / CST
	LENGTH /mm
	PRELOAD /mm
0	REBOUND %
	0

☐ YES ☒ NO	FOAM INSERTS	☐ YES ☒ NO
☐ YES ☒ NO	O-RING ON SHAFT	☐ YES ☒ NO

☐ 3 HOLES	PISTONS	☐ 3 HOLES
☒ 4 HOLES	1.0mm	☒ 4 HOLES
	1.1mm	
	1.2mm	
	OTHERS	

1.4	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.2
-----	--------------	---------------	--------------	-----

Ride	TIRES	Ride
	INSERTS	
LRP	ADDITIVE	LRP
30min	ADDITIVE TIMING	30min

FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT
TREATED AREA			

WHEELS			
S ☐	M ☐	H ☐	HARDNESS
S ☐	M ☐	H ☐	

MOTOR	Lipotech Vario 4.5	TIMING	5?
ROTOR	St.	ARMATURE	

ESC	Hobbywing	BATTERIES	EzPower
-----	-----------	-----------	---------

BODY	Montech Nazda 2	WING	Montech
------	-----------------	------	---------

● ☒ - APPLIED S-SOFT M-MEDIUM H-HARD

FRONT	CASTER	0°	2°	4°	6°	SQUAT	ROLL-CENTER	REAR
DIVE	+0.75	0.00	-0.75	SHIM	/mm	+0.75	0.00	-0.75
	☒	☐	☐	☒		☒	☐	☐
	SHIM	/mm	SHIM	/mm		SHIM	/mm	SHIM
	5.0	RIDE HEIGHT/mm	WHEELBASE/mm	257	RIDE HEIGHT/mm	5.2		

FRONT	REAR
C-HUB	REAR HUB
M ☒	M ☐
H ☐	H ☒
ALU ☐	ALU ☐
STEERING BLOCK	ROLL CENTER UPPER CLAMP
M ☐	
H ☒	
ALU ☐	
OFFSET	OFFSET
STANDARD ☒	STANDARD ☒
6.4	DOWNSTOP/mm
	5.4

TOE /deg.	FINAL TOE IN	3	OUTBOARD TOE	0
OUT 1.5	INBOARD TOE			
SHIM UNDER SHOCK	SHIM	/mm		
SHIM 2				
SHIM FRONT	SHIM REAR			
SHIM 2	SHIM 1.5			
ACKERMANN SHIM	SHIM 1			
ANTI ROLL-BAR	SHIM UNDER SHOCK			
SHIM 2				
SHIM FRONT/REAR	SHIM	/mm		
NO SHIM				
OTHER 0.75				

FRONT	REAR
2	CAMBER /deg.
	2
UPPER SHOCK POSITION	
FRONT ARM	REAR ARM
HARD (H) ☐	HARD (H) ☐
EXTRA-HARD (XH) ☐	EXTRA-HARD (XH) ☐
GRAPHITE (G) ☒	GRAPHITE (G) ☒

BALANCE /g	MOTOR HOLDER	BALANCE /g
	STANDARD ☐	
	OPTION ☒	
ECCENTER /mm		ECCENTER /mm
STANDARD ☒		STANDARD ☐
1		1
DIFE POSITION		DIFE POSITION
UP ☒		UP ☐
DOWN ☐		DOWN ☐
LOWER SUSP. BLOCK		LOWER SUSP. BLOCK
SOLID 1pcs ☐		SOLID 1pcs ☐
SINGLE 2 pcs ☒		SINGLE 2 pcs ☒

COMMENTS
Ecs 52mm front