



# STOCK SETUP

Driver: \_\_\_\_\_

Track/Event: \_\_\_\_\_

Date: \_\_\_\_\_

Car: \_\_\_\_\_

ESC Firmware: \_\_\_\_\_

Traction:

Low  
Medium  
High

Motor: \_\_\_\_\_

Battery: \_\_\_\_\_

Rotor: \_\_\_\_\_

Comments/Results: \_\_\_\_\_

Timing: \_\_\_\_\_

Gearing: \_\_\_\_\_

Settings		1	2	3	4	5	6	7	8	9
1	Running Mode	Forward, Brake	Forward, Reverse with Brake	Forward, Reverse	Blinky Mode* Forward, Brake	Blinky Mode* Forward, Reverse with Brake	Blinky Mode* Forward, Reverse	* In the blinky mode the settings 10-15 are unavaible and deactivated.		
2	Drag Brake Force	0%	5%	10%	15%	20%	25%	30%	100%	User Setting: _____ %
3	Low Voltage Cut-Off Threshold	No Protection	2.6V/Cell	2.8V/Cell	3.0V/Cell	3.2V/Cell	3.4V/Cell	User Setting: _____ V/Cell		
4	Start Mode(Punch)	Level 1	Level 2	Level 3	Level 4	Level 5	Level 6	Level 7	Level 8	Level 9
5	Max Brake Force	12.50%	25%	37.50%	50%	62.50%	75%	87.50%	100%	
6	Max Reverse Force	25%	50%	75%	100%					
7	Initial Brake Force	Drag Brake	0%	20%	40%					
8	Neutral Range	6% (Narrow)	9% (Normal)	12% (Wide)						
9	Over-heat Protection	Enable	Disable							
10	Boost Timing	32°	User Setting: _____ (0°-64°   1° steps)							
11	Boost Start	4000 RPM	User Setting: _____ (1000-15000 RPM   50RPM steps)							
12	Boost Timing Acceleration	350 RPM/def	User Setting: _____ (50-750RPM/def   50RPM steps)							
13	Turbo Timing	12°	User Setting: _____ (0°-40°   1° steps)							
14	Turbo Slope Rate	3°/0.1s	6°/0.1s	12°/0.1s	18°/0.1s	24°/0.1s	Fastest			
15	Turbo Delay	0s/off	0.1s	0.2s	0.3s	0.4s	0.5s	0.6s	0.7s	0.8s