

:: Driver: Team Associated      :: Date: \_\_\_\_\_  
 :: Track: Standard RC8 Setup  
 :: Event: \_\_\_\_\_

## Setup Sheet for Team Associated's RC8

Rev. 2

### :: Front Suspension

anti-roll bar:  
 2.2 - black  
 2.5 - silver  
 2.8 - gold

kickup bushing  
 # 2  
 up  down

steering rack:  
 back  
 mid  
 front

hinge pin bushing  
 # 1  
 up  down

camber: -2 °  
 caster: 16 °  
 toe: 0 °  
 ride height: 27 mm

### :: Rear Suspension

anti-roll bar:  
 2.2 - black  
 2.5 - silver  
 2.8 - gold

anti-squat bushing  
 # 2  
 up  down

wheelbase:  
 long  
 medium  
 short

camber: -2 °  
 toe: 3 °  
 ride height: 27 mm

### :: Front Shocks

spring: 70 rate      piston: 1.6  
 shock fluid: 50 wt.      length: full 108mm

### :: Rear Shocks

spring: 59 rate      piston: 1.6  
 shock fluid: 40 wt.      length: full 125mm

### :: Differentials

front fluid: 5000cst  
 center fluid: 7000cst  
 rear fluid: 3000cst

### :: Wing

location:  forward  back  
 angle:  low  med.  high  
 type: standard

### :: Notes

\_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

### :: Engine

engine: \_\_\_\_\_ restrictor: \_\_\_\_\_  
 muffler: \_\_\_\_\_ temp: \_\_\_\_\_  
 glow plug: \_\_\_\_\_  
 fuel: 30% recommended

### :: Gearing/Clutch

gearing: 16/44  
 clutch shoes: standard  
 clutch spring:  .9mm  1.0mm  1.1mm  
 other: \_\_\_\_\_

### :: Front Tires

tire: \_\_\_\_\_  
 compound: \_\_\_\_\_  
 insert: \_\_\_\_\_  
 wheel: \_\_\_\_\_

### :: Rear Tires

tire: \_\_\_\_\_  
 compound: \_\_\_\_\_  
 insert: \_\_\_\_\_  
 wheel: \_\_\_\_\_

### :: Race and Vehicle Comments

qualify: \_\_\_\_\_ main: \_\_\_\_\_ finish: \_\_\_\_\_ tq:   
 comments: \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

### :: Track Info

smooth:  bumpy:  blue groove:   
 traction:  high  med.  low  
 soft dirt:  grass:  clay:  wet:   
 dusty:  other: \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_