

Setup Sheet for Team Associated's RC8

Rev. 2

:: Front Suspension

anti-roll bar:
 2.2 - black
 2.5 - silver
 2.8 - gold

kickup bushing
 # 2 UP/1 REAR
 up down

steering rack:
 back
 mid
 front

hinge pin bushing
 # 3
 up down

camber: -1
 caster: 14
 toe: 0
 ride height: 30 mm

:: Rear Suspension

anti-roll bar:
 2.2 - black
 2.5 - silver
 2.8 - gold

anti-squat bushing
 # 2
 up down

wheelbase:
 long
 medium
 short

camber: -2.5
 toe: 3
 ride height: 30 mm

:: Front Shocks

spring: AE SILVER piston: 1.4X2 1.1X2
 shock fluid: 50 length: 2MM LIMITER

:: Rear Shocks

spring: AE SILEVR piston: 1.4X2 1.1X2
 shock fluid: 50W length: 4MM LIMITER

:: Differentials

front fluid: 5
 center fluid: 7
 rear fluid: 5

:: Wing

location: forward back
 angle: low med. high
 type: AE

:: Notes

:: Engine

engine: GRP restrictor: 6.5
 muffler: GRP 2053 temp: _____
 glow plug: C5
 fuel: 25% O DONNEL

:: Gearing/Clutch

gearing: 16/44
 clutch shoes: 3 ALLOY
 clutch spring: .9mm 1.0mm 1.1mm
 other: _____

:: Front Tires

tire: PROLINE
 compound: M2
 insert: STD
 wheel: TL

:: Rear Tires

tire: _____
 compound: _____
 insert: _____
 wheel: _____

:: Race and Vehicle Comments

qualify: _____ main: _____ finish: _____ tq:
 comments: ALUMINIUM TOWERS, TOP PLATE, REAR BRAKE
 INITIATES BEFORE FRONT. 50/50 BIAS. J CONCEPTS BODY.
 STOCK CHASSIS BRACES.

:: Track Info

smooth: bumpy: blue groove:
 traction: high med. low
 soft dirt: grass: clay: wet:
 dusty: other: _____