

:: Front End

camber: -1
 toe: 0
 washers: 1
 ride height: 30.5 mm
 bump steer spacer: 2 mm
 axle height: up middle down
 caster: 20° 25° 30°

:: Rear End

camber: -1
 anti-squat: 2
 arm mnt toe: 3.0
 washers: 1
 ride height: 29.5 mm
 near hub carriers: std 0° 0.5° 1° 1.5°
 wheel base: long medium short
 anti-roll bar: none black (soft) silver (med) gold (hard)

:: Front Shocks

spring: Kyo 12mm Red piston: #57 x 3
 shock oil: 35 wt limiter: 5

:: Rear Shocks

spring: Kyo 12mm Red piston: #56 x 3
 shock oil: 30 wt limiter: 2

:: Electronics

motor & wind: Reedy Sonic 6.5
 pinion: 18
 spur gear: 87
 batteries: Reedy 60C LiPo #685
 battery placement: 1 spacer in the front of battery

radio: Airtronics M11x
 throttle / brake epa: 100% / 90%
 throttle / brake expo: 0% / 0%
 esc: LRP SXX V2 TC (3.0 Software) throttle profile: 1/0/0/5
 initial brake: - drag brake: -
 servo: Airtronics 94951 steering expo: 0%

:: Other

body: JConcepts High Flow
 notes: Vents cut out

:: Gear Differential / Ball Differential

gear diff fluid:
 ball diff settings: Super Tight

:: Front Tires

tire: JConcepts Barcode
 compound: Green
 insert: JConcepts
 wheel: JConcepts Hazard

:: Rear Tires

tire: JConcepts Barcode
 compound: Green
 insert: JConcepts
 wheel: JConcepts Hazard

:: Race and Vehicle Comments

qualify: _____ main: _____ finish: _____ tq:
 comments: Rear ballast weight; 3 oz behind battery; All carbon arms; Carbon top plate; 4th hole in rear tower

:: Track Info

smooth: bumpy: blue groove:
 traction: high med. low
 soft dirt: grass: clay: wet:
 dusty: other: _____