

Ride Height: 22mm

Camber: -1

Toe: 0

Arm Type: standard

Tower Type: standard

Caster Block Insert: 5 up

Steering Block: #4

Bulkhead Type: Brass AE

Kick-Up Angle: 25

Wheel Hex: Standard


AE alum servo horn and
alum steering rack. B64
rear blue swaybar used

Anti Roll Bar:

None ☐
White (0.8mm) ☐
Gray (0.9mm) ☐
Blue (1.0mm) ☐
Other: 1.4mm ☒


Steering Plate: standard

Steering Stop Spacing: none



Caster Block Spacing: 1mm

Bump Steer Spacing:




Axle Height:

+3 ☒
+2 ☐
+1 ☐
0 ☐
SCH1256 ☐

Ball Stud Spacing: 1mm



Ball Stud Spacing: 1.5mm



Ride Height: 22mm

Camber: -1

Wheel Hex: standard

CVA Pin Location: inner

Hub Spacing:

Forward ☐ Middle ☐ Back ☒

Shock Mounting Position:

Front of Arm ☒ Rear of Arm ☐

Reedy 22g lipo weight
and AE B64 rear alum
hubs used.

Anti Roll Bar:

None ☐
White (1.2mm) ☐
Gray (1.3mm) ☐
Blue (1.4mm) ☐
Other: 1.0 mm ☒

C Mount Inserts: 1° ☒ 0.5° ☐


Aluminum ☒ Brass ☐

D Mount Inserts: 1° ☒ 0.5° ☐

Aluminum ☒ Brass ☐

Rear Hub Link Setting:

Plastic Hub ☐ Aluminum Hub ☐



Spacing:




Ball Stud Spacing



Ball Stud Spacing 2.5mm

Hub Insert:

0 (0/3↑) ☐
+1 (1/2↑) ☐
+2 (1/2↓) ☐
+3 (0/3↓) ☒



Tower: standard



Radio: 7px

Servo: Reedy 1206

EPA: Throttle: 100 % Brake: 95 %

ESC: Reedy 510r

ESC Settings: custom

Motor: Reedy S Plus Timing: 30

Pinion: 24 Spur: 81

Battery: Reedy Zappers SG 4800

Battery Position: Rear

Drivetrain:

Height: 3mm

Transmission:

☒ 3 Gear ☒ Laydown
☐ 4 Gear ☐ Layback
☐ 4 Gear ☐ Stand up

☐ Ball Diff:


☒ Gear Diff: 10k

Slipper Clutch: Vented AE

of Pads: 2

Shocks:

| | Front | Rear |
|----------------|------------------------------|------------------------|
| Piston: | <u>1.6 AE machined</u> | <u>1.8 AE machined</u> |
| Fluid: | <u>45 AE</u> | <u>32.5 AE</u> |
| Spring: | <u>AE Orange v2</u> | <u>AE Blue v2</u> |
| Limiters: | <u>2</u> | <u>1</u> |
| Stroke: | <u>27</u> | <u>35.5</u> |
| Eyelet Length: | <u>long</u> | <u>short</u> |
| Cup Offset: | <u>9mm</u> | <u>9mm</u> |
| Notes: | <u>AE machined internals</u> | |



Size: Small ☐ Medium ☒ Large ☐ Extra Large ☐

Surface: Dirt ☐ Carpet ☒ Astroturf ☐ Multi Surface ☐

Traction: Low ☐ Medium ☐ High ☒ Very High ☐

Moisture: Dry ☐ Damp ☐ Wet ☐

Condition: Indoor ☒ Outdoor ☐ Dusty ☐ Hard Packed ☐

Bumpy ☐ Grooved ☐ Smooth ☐ Loamy ☐

Temperature: Ambient: 75 Humidity: _____

Notes: _____

Front Tires: PL Wedge T

Front Compound: z3

Front Insert: stock open cell

Rear Tires: PL Prism T

Rear Compound: z3

Rear Insert: stock open cell

Wheel (F/R): AE

Notes: _____

Body: standard

Wing: na

Notes: _____

Servo Weights: yes

None ☐ Aluminum ☐ Steel ☒ Other ☐

Electronic Weights: _____

None ☐ Aluminum ☐ Steel ☒ Other ☐

Total Vehicle Weight: _____